

8300100952
VBH0190RSLDZ

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100952	
Motor	E06002-17	

Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60

Method of obtaining data		ml
Speed (rpm)	min ⁻¹	3650
Power consumption	W	120
Current draw	A	1.0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



8300100952
VBH0190RSLDZ

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Technical description

Size	190 mm
Motor size	60
Rotor surface	Thick-film passivated
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Housing material	PA plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1+
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing; (sealed, without air gap)
Technical features	- Output 10 VDC, max. 10 mA - Locked-rotor detection - Tach output - Speed control - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3,5 mA
Motor protection	Electronic motor protection
With cable	Variable
Protection class assignment	I; If a protective earth is connected by the customer This component for installation may have several local protection classes. This information relates to this component's basic design. The final protection class is based on the component's intended installation and connection.
Conformity with standards	EN 60335-1; EN 60034-1; EN 60204-1; CE




8300100952
VBH0190RSLDZ

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Product drawing



1	Supply line (PWR) PVC AWG20
	3x splice
2	Control wire (CTRL) PVC AWG22
	4x splice




8300100952
VBH0190RSLDZ

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Mounting dimensions




8300100952
VBH0190RSLDZ

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	PWR	L	black	Power supply, phase, see nameplate for voltage range
	PWR	N	blue	Power supply, neutral conductor, see nameplate for voltage range
	PWR	PE	green/yellow	Protective earth
				-
	CTRL	GND	blue	Reference ground for control interface, SELV
	CTRL	IO1	yellow	Function parameterizable Factory setting: Analog input 0-10 V/PWM, Ri=100 kΩ fPWM=1 kHz..10 kHz, function: Speed set value Characteristic curve parameterizable (see input characteristic curve "Input curve 1"), SELV
	CTRL	IO2	white	Function parameterizable Factory setting: Open collector output, Umax=50 VDC, Imax=10 mA, function: Tach output 1 pulse/revolution, SELV
	CTRL	Vout	red	Voltage output 10 VDC +/-3%, Imax=10 mA Short-circuit-proof, power supply for external devices, SELV




8300100952
VBH0190RSLDZ

EC centrifugal module - RadiCal

backward-curved, single-intake
with housing

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-211981-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	1~	230	50	4045	120	1.00	71	78	875	0	515	0.00
2	1~	230	50	3885	120	1.00	66	74	730	220	430	0.88
3	1~	230	50	3650	120	1.00	63	71	490	420	290	1.69
4	1~	230	50	3915	120	1.00	70	77	240	640	140	2.57
5	1~	230	50	3400	71	0.58	67	74	735	0	435	0.00
6	1~	230	50	3400	80	0.66	63	70	640	168	375	0.67
7	1~	230	50	3400	96	0.80	62	69	455	366	270	1.47
8	1~	230	50	3400	78	0.65	66	73	210	483	125	1.94
9	1~	230	50	2800	40	0.32	62	69	605	0	355	0.00
10	1~	230	50	2800	45	0.37	58	66	530	114	310	0.46
11	1~	230	50	2800	54	0.45	57	64	375	249	220	1.00
12	1~	230	50	2800	44	0.36	61	68	170	328	100	1.32
13	1~	230	50	2200	19	0.16	56	63	475	0	280	0.00
14	1~	230	50	2200	22	0.18	52	60	415	70	245	0.28
15	1~	230	50	2200	26	0.22	51	58	295	153	175	0.61
16	1~	230	50	2200	21	0.18	55	62	135	202	80	0.81

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · P_{fs} = Pressure increase

