

AC axial fan

sickle-shaped blades (S series)

bmpapst Datasheet

Nominal data

Type	A2D300-AP06-14		
Motor	M2D074-DF		
Phase		3~	3~
Nominal voltage	VAC	480	480
Wiring		Y	Y
Frequency	Hz	50	60
Method of obtaining data		fa	fa
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	2550	2650
Power consumption	W	220	300
Current draw	A	0.30	0.40
Max. back pressure	Pa	140	120
Max. back pressure	inH2O	0.56	0.48
Max. ambient temperature	°C	75	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change




Technical description

Weight	3.1 kg
Fan size	300 mm
Rotor surface	Painted black
Blade material	Sheet steel, painted black
Number of blades	5
Airflow direction	"V"
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP44
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F2-2
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1

AC axial fan

sickle-shaped blades (S series)

Product drawing




- | | |
|---|------------------------------------|
| 1 | Cable silicone, 4x crimped splices |
| 2 | Direction of air flow "V" |
| 3 | Max. clearance for screw 10 mm |

AC axial fan

sickle-shaped blades (S series)

Connection diagram



Note: Change of rotation direction by reversing two phases


Y	Star connection	L1	black	L2	blue
L3	brown	U1	black	V1	blue
W1	brown	U2	green	V2	white
W2	yellow				



AC axial fan

sickle-shaped blades (S series)

Curves: Air performance 50 Hz



Measurement: LU-42311-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	CFM	inH ₂ O
1	480	50	2550	220	0.30	3180	0	1870	0.00
2	480	50	2485	235	0.32	2850	50	1675	0.20
3	480	50	2440	252	0.34	2445	100	1440	0.40
4	480	50	2395	267	0.36	1925	140	1135	0.56


U = Power supply · f = Frequency · n = Speed (rpm) · P_{θ} = Power consumption · I = Current draw · qv = Air flow · p_{ts} = Pressure increase



AC axial fan

sickle-shaped blades (S series)

Curves: Air performance 60 Hz



Measurement: LU-42312-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH ₂ O
1	480	60	2690	300	0.40	3365	0	1980	0.00
2	480	60	2615	318	0.41	3080	40	1815	0.16
3	480	60	2540	333	0.43	2760	80	1625	0.32
4	480	60	2470	346	0.45	2325	120	1370	0.48

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

