

D4E133-DH61-D1

AC centrifugal fan

forward-curved, dual-intake

with housing (without flange)

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	D4E133-DH61-D1	
Motor	M4E068-BF	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Method of obtaining data		fa
Valid for approval/standard		CE
Speed (rpm)	min ⁻¹	930
Power consumption	W	80
Current draw	A	0.36
Capacitor	µF	2
Capacitor voltage	VDB	400
Capacitor standard		S2 (CE)
Min. back pressure	Pa	0
Min. back pressure	in. wg	0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	55

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC centrifugal fan

forward-curved, dual-intake

with housing (without flange)

Technical description

Weight	2.7 kg
Size	133 mm
Motor size	68
Rotor surface	Unpainted
Impeller material	PA plastic
Housing material	Sheet steel, galvanized
Motor suspension	Motor vibration-damped on both sides
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor mounting	Ball bearing
Speed levels	5
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE




D4E133-DH61-D1

AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Product drawing




1 Cable AWG20, 8x flat push-on receptacle 6.3 x 0.8 with connector housing, 1x crimped ring terminal Ø 5.2



AC centrifugal fan

forward-curved, dual-intake
with housing (without flange)

Connection diagram




Note: High speed (step IV); low speed (step I)

1	= N = blue
2	brown
3	yellow
4	Step I black 1 / white
5	Step II black 2 / red
6	Step III black 3 / gray
7	L1
8	Step IV black 4 / orange
9	Step V black 5 / black
10	PE (green/yellow)



Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-24566-1
Measurement: LU-24567-1
Measurement: LU-24568-1
Measurement: LU-24569-1
Measurement: LU-24570-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Stage	Wired	U	f	n	Pe	I	qv	Pfs	qv	Pfs
			V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	5	1~	230	50	930	80	0.36	695	0	410	0.00
2	5	1~	230	50	1135	74	0.32	590	40	345	0.16
3	5	1~	230	50	1275	69	0.30	395	80	230	0.32
4	5	1~	230	50	1345	67	0.30	240	100	140	0.40
5	4	1~	230	50	820	68	0.30	580	0	340	0.00
6	4	1~	230	50	995	63	0.28	520	31	305	0.12
7	4	1~	230	50	1205	57	0.25	365	69	215	0.28
8	4	1~	230	50	1300	54	0.24	230	92	135	0.37
9	3	1~	230	50	690	61	0.27	480	0	285	0.00
10	3	1~	230	50	900	57	0.26	450	24	265	0.10
11	3	1~	230	50	1125	51	0.23	345	62	205	0.25
12	3	1~	230	50	1250	48	0.21	225	86	130	0.35
13	2	1~	230	50	565	53	0.24	385	0	225	0.00
14	2	1~	230	50	755	50	0.23	370	19	215	0.08
15	2	1~	230	50	995	46	0.21	300	47	180	0.19
16	2	1~	230	50	1160	42	0.19	205	73	120	0.29
17	1	1~	230	50	420	46	0.21	285	0	170	0.00
18	1	1~	230	50	545	45	0.21	275	9	160	0.04
19	1	1~	230	50	810	42	0.20	245	30	145	0.12
20	1	1~	230	50	1030	38	0.18	185	58	110	0.23

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · Pe = Power consumption · I = Current draw · qv = Air flow · Pfs = Pressure increase

