


Research Data

Air-flow rate[m ³ /h]	4952
Pressure[Pa]	471.5
Pressure Type	Psta
Power supply	all
Density[m ³ /h]	1.205

Label

Code	PC636ATEX
Voltage[V]	400
Phases	3
Current[A]	
Poles	6
Weight[kg]	125
Frequency[Hz]	50
Speed[rpm]	900
Power[kW]	3
IP	55
INS	



PMM-Q636ATEX

PP-el antistatic welded housing -PP-el/INOX welded impeller - epoxy painted motor support - stainless steel screws

Certificazioni








Table engines



Class IE	IE1	IE2	IE3
Size	132S	132S	132S
Power[kW]	3	3	3
Current[A]	6.9	6.84	6.9
Voltage[V]	400	400	400
Cos φ	0.76	0.76	0.74
n	0.79	0.833	0.856

Working point

Q [m ³ /h]	4952
P _{sta} [Pa]	471.5
P _{tot} [Pa]	517.7
P _{in} [kW] [W]	1215.
n _{sta}	0.534
n _{tot}	0.586
Rpm	900




Dimensions




A	B	C	D	E	F	G	H	I	L	N	Ø	P	R
406	573	80	450	350	418	50	800	492	340	337	14	270	373
S	T	U	V	X	X1	X2	Y	Z					
330	400	773	50	25	40	15	18	480					

Configurations & cad


LG 0°




LG 45°




LG 90°




LG 135°




LG 180°




LG 225°




LG 270°




LG 315°




RD 0°




RD 45°




RD 90°




RD 135°




RD 180°



RD 225°



RD 270°



RD 315°

