

R1G175-AB63-02

EC centrifugal fan

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Nominal data

Type	R1G175-AB63-02	
Motor	M1G055-BD	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		fa
Speed (rpm)	min ⁻¹	3100
Power consumption	W	34
Current draw	A	1.6
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



R1G175-AB63-02

EC centrifugal fan

backward-curved, single-intake


Technical description

Weight	0.74 kg
Size	175 mm
Motor size	55
Rotor surface	Thick-film passivated
Impeller material	PA 6.6 plastic, glass-fiber reinforced
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP20
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F0; H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Technical features	- Tach output - Motor current limitation - Soft start - Control input 0-10 VDC / PWM
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 55022 (Class B, household environment)
Motor protection	Reverse polarity and locked-rotor protection
With cable	Variable
Conformity with standards	EN 60950-1
Approval	EAC; UL 1004-1; CSA C22.2 No. 77



EC centrifugal fan

backward-curved, single-intake




1	Cable AWG20, 4x crimped splices
2	Accessory part: inlet ring 09576-2-4013 not included in scope of delivery
3	Max. clearance for screw 6 mm


Connection diagram

Customer circuit

full speed




adjustable speed




10 V → n = max
1 V → n = min
<1 V → n = 0
safe start
at Unom -30%
from 4 V Ucontr.

speed adjustable with fixed resistor




speed adjustable via PWM 1-10 kHz




100% PWM → n = max
10% PWM → n = min
<10% PWM → n = 0
safe start
at Unom -30%
from 40% PWM

Set value requirement via temperature controller




Connection

Fan/Motor



No.	Conn.	Designation	Color	Function/assignment
1	4	Un +24 VDC	red	Power supply 24 VDC, maximum ripple 3.5%
1	3	0-10 VDC	yellow	Control input Re > 100 K
1	2	DUE	white	Tach output, 2 pulses per revolution, Isink max = 10 mA
1	1	GND	blue	Reference ground

Curves: Air performance



Measurement: LU-44776-1
 Measurement: LU-44775-1
 Measurement: LU-44777-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	q _V	p _{fs}	q _V	p _{fs}
	V	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	28	3375	46	1.83	605	0	355	0.00
2	28	3170	48	1.97	470	123	275	0.49
3	28	3105	49	2.01	325	231	190	0.93
4	28	3255	47	1.91	155	325	90	1.30
5	24	3100	34	1.60	555	0	330	0.00
6	24	2915	39	1.79	435	100	255	0.40
7	24	2885	39	1.82	300	200	175	0.80
8	24	3010	37	1.69	145	275	85	1.10
9	16	2320	16	1.10	420	0	245	0.00
10	16	2225	17	1.21	330	60	195	0.24
11	16	2205	18	1.24	230	116	135	0.47
12	16	2270	16	1.15	110	158	65	0.63

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_V = Air flow · p_{fs} = Pressure increase