

EC centrifugal fan

backward curved, single inlet



Nominal data

Type	R3G500-AP15-03	
Motor	M3G150-FF	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Type of data definition		ml
State		prelim.
Speed	min ⁻¹	1780
Power input	W	2870
Current draw	A	4.4
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	45

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	Yes
Specific ratio*	1.01

* Specific ratio = 1 + p_{fs} / 100 000 Pa

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}	%	64.7	52.3	56.3
Efficiency grade N		70.4	58	62
Power input P _{ed}	kW	2.86		
Air flow q _v	m³/h	8020		
Pressure increase p _{fs}	Pa	789		
Speed n	min ⁻¹	1790		

Data definition with optimum efficiency. LU-111345
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.




Technical features

Mass	23.6 kg
Size	500 mm
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium
Material of impeller	Aluminium sheet
Number of blades	7
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F4-1
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on bottom
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC - Output 20 VDC - Output for slave 0-10 V - Input for sensor 0-10 V or 4-20 mA - Alarm relay - Integrated PID controller - Motor current limit - PFC, passive - RS485 ebmBUS - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2
EMC interference emission	Acc. to EN 61000-6-3
Electrical leads	Via terminal box
Motor protection	Reverse polarity and locked-rotor protection
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	CE
Approval	CSA C22.2 Nr.77; EAC; UL 2111; VDE

EC centrifugal fan

backward curved, single inlet

Product drawing




- | | |
|---|--|
| 1 | Cable diameter: min. 4 mm, max. 10 mm |
| 2 | Accessory part: Inlet nozzle 64025-2-4013 not included in delivery, other inlet nozzles on request |
| 3 | Depth of screw max. 25 mm |

EC centrifugal fan


backward curved, single inlet

Connection screen



No.	Conn.	Designation	Function / assignment
PE		PE	Protective earth connection
KL1	1, 2, 3	L1, L2, L3	Supply voltage, 50/60 Hz
KL2	1	NC	Floating status message contact, normally closed connection
KL2	2	COM	Floating status message contact, changeover contact, common connection (2 A, max. 250 VAC, min. 10 mA, AC1)
KL2	3	NO	Floating status message contact, normally open connection
KL3	1	OUT	Analog output, 0-10 VDC, max. 3 mA, SELV, output of the current level control coefficient: 1 V equates to 10 % level control coefficient. 10 V equate to 100 % level control coefficient.
KL3	2, 8	GND	Reference mass for control interface, SELV
KL3	3, 7	0-10 V	Use control / actual value input 0-10 VDC, impedance 100 kΩ only as alternative to 4-20 mA input, SELV
KL3	4	+10 V	Voltage output 10 VDC (+/-3 %), max. 10 mA, supply voltage for ext. devices (e.g. potentiometers), SELV
KL3	5	+20 V	Voltage output 20 VDC (+25 %/-10 %), max. 50 mA, supply voltage for ext. devices (e.g. sensors), SELV
KL3	6	4-20 mA	Use control / actual value input 4-20 mA, impedance 100 Ω, only as alternative to 0-10 V input, SELV
KL3	9, 11	RSB	RS485 interface for ebmBus, RSB, SELV
KL3	10, 12	RSA	RS485 interface for ebmBus, RSA, SELV

Charts: Air flow 50 Hz



Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L_{wA} measured as per ISO 13347 / L_{pA} measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{rs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa
1	400	50	1780	1735	2.65	87	94	98	12090	0
2	400	50	1780	2484	3.78	78	86	90	10120	500
3	400	50	1780	2870	4.40	73	80	86	7775	850
4	400	50	1780	2389	3.62	78	85	91	4005	1050
5	400	50	1500	973	1.50	80	89	94	10130	0
6	400	50	1500	1373	2.11	72	80	86	8445	358
7	400	50	1500	1575	2.41	69	76	82	6460	606
8	400	50	1500	1329	2.05	72	80	85	3345	752
9	400	50	1200	499	0.86	75	82	88	8170	0
10	400	50	1200	711	1.13	67	74	81	6745	228
11	400	50	1200	798	1.28	63	70	76	5125	380
12	400	50	1200	677	1.08	66	73	79	2665	477
13	400	50	900	225	0.44	66	74	82	6100	0
14	400	50	900	303	0.57	59	66	72	5050	128
15	400	50	900	338	0.63	57	63	68	3835	212
16	400	50	900	299	0.57	58	65	71	2005	271

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · LwA_{out} = Sound power level outlet side
 q_v = Air flow · p_{rs} = Pressure increase