

W1G200-HH77-52

EC axial fan

sickle-shaped blades (S series)



ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	W1G200-HH77-52	
Motor	M1G074-BF	
Nominal voltage	VDC	24
Nominal voltage range	VDC	16 .. 28
Method of obtaining data		fa
Speed (rpm)		
Power consumption		
Current draw		
Max. back pressure		
Min. ambient temperature		
Max. ambient temperature		

mI = Max. load ·
Subject to change



W1G200-HH77-52

EC axial fan

sickle-shaped blades (S series)

Technical description

Weight	2.13 kg
Motor size	200 mm
Rotor surface	Painted black
Blade material	Sheet steel, painted black
Wall ring material	Die-cast aluminum
Number of blades	9
Direction of air flow	«V»
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP 42
Insulation class	«B»
Humidity protection class	F0
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	
Condensation drainage holes	
Mode	
Motor protection	
Technical features	
	- Control input 0-10 VDC / PWM
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	55022 (class B)
Electrical hookup	terminal box
Motor protection	reverse polarity and locked-rotor protection
Conformity with standards	EN 60335-1
Approval	GOST; UL 1004-1; CSA C22.2 No. 77




W1G200-HH77-52

EC axial fan

sickle-shaped blades (S series)


Product drawing



1	Conn.
1.1	UN +24 VDC (red)
1.2	GND (blue)
1.3	DUE
1.4	0-10
2	Voltage




Connection diagram



№	Conn.			
1	1			
1	2			
1	3	Tach	white	Tach output, 3 pulses/revolution, Isink max. = 10 mA
1	4	GND	blue	Common

Curves: Air performance



Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters must be checked in the installed unit.

Measured values

	U					
	V					
1	28	3285	73	2.91	1205	0
2	28	3190	76	3.01	1115	38
3	28					72
4	28					110
5	24					0
6	24	2915	57	2.67	1015	30
7	24	2860	60	2.76	915	60
8	24	2785	62	2.88	740	90
9	16	2285	28	2.08	835	0
10	16	2245	28	2.09	770	18
11	16	2200	29	2.13	700	35
12	16	2145	30	2.18	565	53

U = Supply voltage · n = Speed · P

ed = Power consumption · I = Current draw · qv = Air flow · p

Δp = Pressure increase