

W2S130-AA03-90

## AC axial compact fan



**ebm-papst Muldingen GmbH & Co. KG**

Bachmühle 2 · D-74673 Muldingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

### Nominal data

|                             |                    |      |      |      |      |
|-----------------------------|--------------------|------|------|------|------|
| Type                        | W2S130-AA03-90     |      |      |      |      |
| Motor                       | M2S052-CA          |      |      |      |      |
| Phase                       |                    | 1~   | 1~   | 1~   | 1~   |
| Nominal voltage             | VAC                | 115  | 115  | 230  | 230  |
| Frequency                   | Hz                 | 50   | 60   | 50   | 60   |
| Method of obtaining data    |                    | fa   | fa   | fa   | fa   |
| Valid for approval/standard |                    | CE   | CE   | CE   | CE   |
| Speed (rpm)                 | min <sup>-1</sup>  | 2800 | 3200 | 2800 | 3200 |
| Power consumption           | W                  | 45   | 42   | 45   | 42   |
| Current draw                | A                  | 0.62 | 0.52 | 0.31 | 0.26 |
| Max. back pressure          | Pa                 | 60   | 75   | 60   | 75   |
| Max. back pressure          | inH <sub>2</sub> O | 0.24 | 0.3  | 0.24 | 0.3  |
| Min. ambient temperature    | °C                 | -25  | -25  | -25  | -25  |
| Max. ambient temperature    | °C                 | 40   | 70   | 40   | 70   |
| Starting current            | A                  | 0.9  | 0.76 | 0.45 | 0.38 |


ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change



## Technical description


|                                                                            |                                                        |
|----------------------------------------------------------------------------|--------------------------------------------------------|
| Weight                                                                     | 1.1 kg                                                 |
| Fan size                                                                   | 130 mm                                                 |
| Rotor surface                                                              | Rotor open, painted black                              |
| Impeller material                                                          | Sheet steel, painted black                             |
| Fan housing material                                                       | Die-cast aluminum, painted black                       |
| Number of blades                                                           | 7                                                      |
| Airflow direction                                                          | "V"                                                    |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                  |
| Degree of protection                                                       | IP20                                                   |
| Insulation class                                                           | "B"                                                    |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                |
| Installation position                                                      | Any                                                    |
| Condensation drainage holes                                                | None                                                   |
| Mode                                                                       | S1                                                     |
| Motor bearing                                                              | Ball bearing                                           |
| Speed levels                                                               | Dual-voltage                                           |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                              |
| Motor protection                                                           | Thermal overload protector (TOP) with basic insulation |
| Protection class                                                           | I (with customer connection of protective earth)       |
| Conformity with standards                                                  | EN 60335-1; CE                                         |
| Approval                                                                   | UL 507; CSA C22.2 No. 113                              |

## Product drawing




- |   |                                          |
|---|------------------------------------------|
| 1 | Cable AWG22, 4x galvanized wire ends     |
| 2 | TOP wires AWG20, 2x galvanized wire ends |
| 3 | Direction of air flow "V"                |

Connection diagram



|     |           |   |              |   |              |
|-----|-----------|---|--------------|---|--------------|
|     | 115 V     | L | black + gray | N | blue + brown |
| TOP | 2x yellow |   |              |   |              |


Connection diagram 2



|     |           |   |              |   |      |
|-----|-----------|---|--------------|---|------|
|     | 230 V     | L | black        | N | blue |
| TOP | 2x yellow |   | brown + gray |   |      |



## Curves: Air performance 50 Hz



Measurement: LU-133512-1  
 Measurement: LU-133510-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.


## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | qv   | p <sub>fs</sub> | qv  | p <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|------|-----------------|-----|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h | Pa              | CFM | inH <sub>2</sub> O |
| 1 | 230 | 50 | 2800              | 45             | 0.31 | 345  | 0               | 200 | 0.00               |
| 2 | 230 | 50 | 2790              | 45             | 0.31 | 315  | 20              | 185 | 0.08               |
| 3 | 230 | 50 | 2775              | 45             | 0.30 | 280  | 40              | 165 | 0.16               |
| 4 | 230 | 50 | 2770              | 45             | 0.30 | 210  | 60              | 125 | 0.24               |
| 5 | 115 | 50 | 2800              | 45             | 0.62 | 345  | 0               | 205 | 0.00               |
| 6 | 115 | 50 | 2790              | 45             | 0.62 | 315  | 20              | 185 | 0.08               |
| 7 | 115 | 50 | 2775              | 45             | 0.60 | 280  | 40              | 165 | 0.16               |
| 8 | 115 | 50 | 2770              | 45             | 0.60 | 210  | 60              | 125 | 0.24               |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · qv = Air flow · p<sub>fs</sub> = Pressure increase



## Curves: Air performance 60 Hz



Measurement: LU-133514-1  
Measurement: LU-133511-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub> | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|----------------|-----------------|----------------|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h           | Pa              | CFM            | inH <sub>2</sub> O |
| 1 | 230 | 60 | 3200              | 42             | 0.26 | 395            | 0               | 230            | 0.00               |
| 2 | 230 | 60 | 3180              | 42             | 0.25 | 365            | 27              | 215            | 0.11               |
| 3 | 230 | 60 | 3150              | 43             | 0.25 | 330            | 50              | 195            | 0.20               |
| 4 | 230 | 60 | 3125              | 44             | 0.26 | 250            | 75              | 150            | 0.30               |
| 5 | 115 | 60 | 3200              | 42             | 0.52 | 400            | 0               | 235            | 0.00               |
| 6 | 115 | 60 | 3180              | 42             | 0.50 | 365            | 25              | 215            | 0.10               |
| 7 | 115 | 60 | 3150              | 43             | 0.50 | 325            | 50              | 190            | 0.20               |
| 8 | 115 | 60 | 3125              | 44             | 0.52 | 250            | 75              | 145            | 0.30               |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

