

W3G910-GS35-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	W3G910-GS35-03	
Motor	M3G150-FF	

Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60

Method of obtaining data		ml
Status		prelim.
Speed (rpm)	min ⁻¹	800
Power consumption	W	1700
Current draw	A	2.7
Max. back pressure	Pa	150
Max. back pressure	in. wg	0.6
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	46.9	35	09 Power consumption P_{ed}	kW	1.6
02 Measurement category	A			09 Air flow q_v	m ³ /h	18445
03 Efficiency category	Static			09 Pressure increase p_{fs}	Pa	143
04 Efficiency grade N	51.9	40		10 Speed (rpm) n	min ⁻¹	805
05 Variable speed drive	Yes			11 Specific ratio*		1.00

Data obtained at optimum efficiency level.

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$

LU-202135

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).



EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Technical description

Weight	45.9 kg
Size	910 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum, painted gray
Blade material	Sheet aluminum insert, sprayed with PP plastic
Fan housing material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Blade pitch	0°
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H2
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.3 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Reverse polarity and locked-rotor protection
Protection class	I (with customer connection of protective earth)



W3G910-GS35-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Conformity with standards	EN 61800-5-1; CE
Approval	UL 1004-7 + 60730-1; CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC




EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Product drawing



1	Airflow direction "V"
2	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm (The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)
3	Tightening torque 1.5 ± 0.2 Nm
4	Attachment holes for FlowGrid (91000-2-2957 not included in scope of delivery)




EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Connection diagram




No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V / PWM, Ri=100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Fan modulation level Characteristic curve parameterizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve



Terminal/plug assignment

configurable IO functions: normal/ inverse		MODBUS Register for IO mode configuration		electrical specification		configurable IO mode		CON2
						Din1 (active high): digital input	Din1 0-10V/PWM: analog input	
IO1		active: applied voltage 3.5-50VDC, SELV	not active: pin open or applied voltage < 1.5VDC					
		RI = 100k, characteristic curve parameterizable, f_PWM = 1k..10KHz, SELV						
		Umax = 50VDC, Imax = 20mA, SELV						
		Umax = 50VDC, Imax = 20mA, SELV						
IO2		active: applied voltage 3.5-50VDC, SELV	not active: pin open or applied voltage < 1.5VDC					
		RI = 100k, characteristic curve parameterizable, f_PWM = 1k..10KHz, SELV						
		RI = 125R, characteristic curve parameterizable, SELV						
		active: applied voltage 3.5-50VDC, SELV	not active: pin open or applied voltage < 1.5VDC					
IO3		active: applied voltage 3.5-50VDC, SELV	not active: pin open or applied voltage < 1.5VDC					
		active: applied voltage < 1.5VDC, SELV						
		PWM = 40Hz - 10KHz, characteristics parameterizable	active: pin open or applied voltage < 1.5VDC, SELV					
		40Hz - 10KHz, characteristics parameterizable	active: applied voltage < 1.5VDC, SELV					
RSA		active: applied voltage 3.5-50VDC	not active: pin open or applied voltage < 1.5VDC, SELV					
		function parameterizable, max. 5mA, max output frequency 300Hz, SELV						
		0-10V max. 5mA, max output frequency 300Hz, SELV						
		0-10V max. 5mA, max output frequency 300Hz, SELV						
RSB		MODBUS RTU, specification V6.3, SELV						
Vout		voltage output						
		alternatively: Input auxiliary power supply for parameterization via RS485 MODBUS RTU without line voltage						

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-202135-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{ts}	q _v	p _{ts}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	3~	400	50	800	1094	1.83	65	72	72	27905	0	16425	0.00
2	3~	400	50	800	1294	2.11	64	71	71	24995	50	14710	0.20
3	3~	400	50	800	1496	2.40	64	71	71	21885	100	12880	0.40
4	3~	400	50	800	1700	2.70	70	77	77	17165	150	10105	0.60
5	3~	400	50	700	719	1.20	62	69	69	24265	0	14280	0.00
6	3~	400	50	700	848	1.38	61	67	68	21720	38	12785	0.15
7	3~	400	50	700	984	1.58	61	67	67	19030	76	11200	0.31
8	3~	400	50	700	1119	1.77	66	73	73	14910	113	8775	0.45
9	3~	400	50	600	453	0.76	58	65	65	20795	0	12240	0.00
10	3~	400	50	600	534	0.87	57	64	64	18615	28	10955	0.11
11	3~	400	50	600	620	0.99	57	64	63	16310	56	9600	0.22
12	3~	400	50	600	705	1.12	63	69	69	12780	83	7520	0.33
13	3~	400	50	500	262	0.44	53	60	60	17330	0	10200	0.00
14	3~	400	50	500	309	0.50	52	59	59	15515	19	9130	0.08
15	3~	400	50	500	359	0.57	52	59	59	13595	39	8000	0.16
16	3~	400	50	500	408	0.65	58	65	65	10650	58	6265	0.23

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{ts} = Pressure increase

