KARTA KATALOGOWA

4184 NX

Wentylator osiowy DC

Producent: ebm-papst

Dane znamionowe

Napięcie znamionowe	**24 V DC (12…29 V DC)**
Prędkość obrotowa	**3200 obr/min**
Pobór mocy	**4,5 W**
Wydajność	**180 m³/h**
Maks. ciśnienie statyczne	**92 Pa**
Poziom ciśnienia akustycznego	**49 dB(A)**
Poziom mocy akustycznej	**5,7 B**
Temperatura otoczenia	**−30…+75 °C**

Budowa

Wymiary	**119 × 119 × 38 mm**
Materiał wirnika	**tworzywo PA wzmocnione włóknem szklanym**
Obudowa	**metal**
Masa	**0,390 kg**

Charakterystyka przepływowa



Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
Producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

DC axial fan

Series 4100 N 119 x 119 x 38

- **General description:** DC fan with electronically commutated external rotor motor. Commutation electronics completely integrated. Optional Vario-Pro: Highly adaptable software configuration of the fan enables a tailor-made solution to the specific requirements of your applications.
- **Impeller material:** Fiberglass-reinforced PA plastic
- **Housing material:** Metal

Nominal data		Voltage	Voltage range VDC	Air flow	Speed	Power consumption	Sound level	Sound pressure level	Ambient temperature	L10 service life at 40 °C	L10 service life at max. temp.	Weight
Type	**Motor**	**VDC**	**VDC**	**m³/h**	**1/min**	**W**	**Bel**	**dB(A)**	**°C**	**h**	**h**	**kg**
4184 NX	--	24	12 - 29	180	3200	4.5	5.7	49	-30 .. 75	85000	37500	0.390

Subject to modification

Characteristic: Pressure over air flow



DC axial fan

Series 4100 N 119 x 119 x 38

Specific drawing



Technical description

- **General description:** DC fan with electronically commutated external rotor motor. Commutation electronics completely integrated. Optional Vario-Pro: Highly adaptable software configuration of the fan enables a tailor-made solution to the specific requirements of your applications.
- **Housing material:** Metal
- **Direction of rotation:** Right, looking at rotor
- **Electrical connection:** 2 flat plugs 2.8 x 0.5 mm. Optionally also available with strands. Housing with grounding lug for screw M4 x 8 (TORX).
- **Approvals:** VDE, CSA, UL, CE
- **Impeller material:** Fiberglass-reinforced PA plastic
- **Bearings:** Ball bearings
- **Direction of air flow:** Inlet over bars
- **Motor protection:** Reverse-polarity protected. The fan runs only if the polarity is correct.
- **Option:** Speed signal, alarm signal

Contact

ebm-papst St. Georgen GmbH & Co. KG
Hermann-Papst-Straße 1
D-78112 St. Georgen
Phone +49 (0) 7724 / 81-0
Fax +49 (0) 7724 / 81-1309
info2@de.ebmpapst.com
www.ebmpapst.com