

KARTA KATALOGOWA

4412 M

Wentylator osiowy kompaktowy DC

Producent: ebm-papst


Dane znamionowe


Napięcie znamionowe	12 V DC (7...14 V DC)
Prędkość obrotowa	3300 obr/min
Pobór mocy	4,2 W
Wydajność	184 m³/h
Maks. ciśnienie statyczne	88 Pa
Poziom ciśnienia akustycznego	42 dB(A)
Poziom mocy akustycznej	5,3 B
Temperatura otoczenia	-20...+70 °C

Budowa

Wymiary	119 × 119 × 38 mm
Materiał wirnika	tworzywo PBT wzmocnione włóknem szklanym
Obudowa	tworzywo PBT wzmocnione włóknem szklanym
Kierunek obrotów	w prawo, patrząc na wirnik
Kierunek przepływu	wydmuch przez żebra
Zabezpieczenie silnika	ochrona przed odwrotną polaryzacją i zablokowaniem wirnika
Łożyskowanie	kulkowe
Podłączenie	przewody AWG 24, odizolowane i ocynowane
Trwałość L10 (40 °C)	65000 h
Masa	0,250 kg

Charakterystyka przepływowa

Charts: Air flow



Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
 Producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
 biuro@luftberg.pl · www.luftberg.pl

4412 M

DC axial compact fan


ebm-papst St. Georgen GmbH & Co. KG

Hermann-Papst-Straße 1

D-78112 St. Georgen

Phone +49 7724 81-0

Fax +49 7724 81-1309

info2@de.ebmpapst.com

www.ebmpapst.com

Nominal data

Type	4412 M	
Nominal voltage	VDC	12
Nominal voltage range	VDC	7 .. 14
Speed	min ⁻¹	3300
Power input	W	4.2
Min. ambient temperature	°C	-20
Max. ambient temperature	°C	70
Air flow	m ³ /h	184
Sound power level	B	5.3
Sound pressure level	dB(A)	42

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations



4412 M

DC axial compact fan


Technical features

Dimensions	119 x 119 x 38 mm
General description	Particular design features: Innovative impeller with winglets for low noise. Control inputs and alarm and speed signals available on request. High-speed version with 5000 rpm, standard models available with /2 and PWM. General features: Material: fibreglass-reinforced plastic. Impeller PA, housing PBT. Electronic commutation completely integrated. Protected against reverse polarity and locking. Connection via single strands AWG 24, TR 64, bared and tin-plated. Air exhaust over bars. Rotational direction clockwise looking at rotor. Mass: 270 g.
Connection line	Single strands AWG 24, TR 64, bared and tin-plated.
Direction of rotation	Right, looking at rotor
Direction of air flow	Air exhaust over bars
Bearing	Ball bearings
Lifetime L10 at 40 °C	65000 h
Lifetime L10 at 70 °C	32500 h
Lifetime L10 at maximum temperature	32500 h
Mass	0.250 kg
Housing material	Fiberglass-reinforced PBT plastic
Material of impeller	Fiberglass-reinforced PBT plastic
Motor protection	Protected against reverse polarity and locking.

4412 M

DC axial compact fan

Product drawing



4412 M

DC axial compact fan

Charts: Air flow

