

KARTA KATALOGOWA

4414/2HH

Wentylator osiowy kompaktowy DC

Producent: ebm-papst




Dane znamionowe

Napięcie znamionowe	24 V DC (18...28 V DC)
Prędkość obrotowa	5000 obr/min
Pobór mocy	12 W
Pobór prądu	500 mA
Wydajność	280 m³/h
Maks. ciśnienie statyczne	208 Pa
Poziom ciśnienia akustycznego	55 dB(A)
Poziom mocy akustycznej	6,4 B
Temperatura otoczenia	-20...+70 °C

Budowa

Wymiary	119 × 119 × 38 mm
Materiał wirnika	tworzywo sztuczne
Obudowa	tworzywo sztuczne
Kierunek przepływu	wydmuch przez żebra
Łożyskowanie	kulkowe
Podłączenie	przewody
Trwałość L10 (40 °C)	50000 h

Charakterystyka przepływowa



Dane na okładce odczytane z karty produktu ebm-papst (oryginał na kolejnych stronach).
 Producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
 biuro@luftberg.pl · www.luftberg.pl

Product Data Sheet**9693530215****VWC0119AUGBS****4414/2HH****ebmpapst**

The engineer's choice



Product Data Sheet

9693530215
VWC0119AUGBS
4414/2HH

4414/2HH

INDEX

1	General	3
2	Mechanics	3
2.1	General.....	3
2.2	Connections.....	3
3	Operating Data	4
3.1	Electrical Operating Data	4
3.2	Electrical Interface - Output.....	5
3.3	Electrical Features	6
3.4	Aerodynamics	7
3.5	Sound Data.....	8
4	Environment.....	8
4.1	General.....	8
4.2	Climatic Requirements	8
5	Safety.....	9
5.1	Electrical Safety	9
5.2	Approval Tests	9
6	Reliability.....	9
6.1	General.....	9

Product Data Sheet
9693530215
 VWC0119AUGBS
 4414/2HH

1 General


Fan type	Fan	
Rotating direction looking at rotor	Clockwise	
Airflow direction	Air outlet over struts	
Bearing system	Ball bearing	
Mounting position - shaft	Any	

2 Mechanics
2.1 General

Width	119,0 mm	
Height	119,0 mm	
Depth	38,0 mm	
Mass	0,270 kg	
Housing material	Plastic	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges	Wire outlet corner: 80 Ncm Remaining corners: 80 Ncm	
Screw size	ISO 4762 - M4 degreased, without an additional brace and without washer	

2.2 Connections

Electrical connection	Wires	
Lead wire length	L = 310 mm	
Tolerance	+/- 10,0 mm	



Wire	Color	Operation	Wire size	Insulation diameter
1	red	+ UB	AWG 24	1,10 mm
2	blue	- GND	AWG 24	1,10 mm
3	white	Tacho	AWG 24	1,10 mm

The auxiliaries shown on the schematic diagram (which are required for the intended use) are not part of our delivery.

Product Data Sheet
9693530215
 VWC0119AUGBS
 4414/2HH

3 Operating Data
3.1 Electrical Operating Data

Measurement conditions: Normal air density = 1,2 kg/m³; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified). In the intake and outlet area should not be any solid obstruction within 0,5 m.



Δp = 0: corresp. to free air flow (see chapter aerodynamics)
 I: corresp. to arithm. mean current value

Features	Condition	Symbol	Values		
Voltage range		U	18,0 V		28,0 V
Nominal voltage		U _N		24,0 V	
Power consumption	Δp = 0	P	7,3 W	12 W	11,8 W
Tolerance	0010		+/- 17,5 %	+/- 25,0 %	+/- 25,0 %
Current consumption	Δp = 0	I	405 mA	500 mA	420 mA
Tolerance	0010		+/- 17,5 %	+/- 25,0 %	+/- 25,0 %
Speed	Δp = 0	n	4.300 1/min	5.000 1/min	5.000 1/min
Tolerance	0010		+/- 12,5 %	+/- 3,0 %	+/- 3,0 %
Starting current consumption				2.750 mA	

Product Data Sheet
9693530215
 VWC0119AUGBS
 4414/2HH


3.2 Electrical Interface - Output

Tacho type	/2 (open collector)
------------	---------------------

Signal-Ausgangsspannung / Signal output voltage

Lüfter-Drehzahl / Fan speed


$$R_a = \frac{U_{BS} - U_{s\ low}}{I_{sink}}$$

Lüfter / Fan Kunde / Customer




Features	Note	Values
Tacho operating voltage	U_{BS}	60 V
Tacho signal Low	$U_{s\ low}$	I_{sink} : 2 mA $\leq 0,4$ V
Tacho signal High	$U_{s\ high}$	I_{source} : 0 mA 60 V
Maximum sink current	I_{sink}	≤ 4 mA
External resistor	External resistor R_a from U_{BS} to U_s required. All voltages measured to GND.	
Tacho frequency	$(2 \times n) / 60$	
Tacho isolated from motor	No	
Slew rate		$\Rightarrow 0,5$ V/ μ s

n = revolutions per minute (1/min)

Product Data Sheet
9693530215
 VWC0119AUGBS
 4414/2HH

3.3 Electrical Features

Electronic function	Speed-Controlled	
Reversed polarity protection	Rectifying diode	
Max. residual current at U_N	$I_F \leq 100 \mu A$	
Locked rotor protection	Auto restart	
Locked rotor current at U_N	I_{block} approx. 2.750 mA	
Clock signal at locked rotor	t_3 / t_4 typical: 0,25 s / 20 s	



Product Data Sheet
9693530215
 VWC0119AUGBS
 4414/2HH

3.4 Aerodynamics

Measurement conditions:

Measured with a double chamber intake rig acc. to DIN EN ISO 5801.

 Normal air density = 1,2 kg/m³; Temperature 23°C +/- 3°C;


In the intake and outlet area should not be any solid obstruction within 0,5 m. Motor shaft horizontal.

The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions.

a.) Operation condition:

5.000 1/min at free air flow

Max. free-air flow ($\Delta p = 0 / \dot{V} = \max.$)	280,0 m ³ /h	
Max. static pressure ($\Delta p = \max. / \dot{V} = 0$)	208 Pa	



Product Data Sheet
9693530215
 VWC0119AUGBS
 4414/2HH

3.5 Sound Data

Measurement conditions: Sound pressure level: 1 meter distance between microphone and the air intake.
 Sound power level: Acc. to DIN 45635 part 38 (ISO 10302)
 Measured in a semianchoic chamber with a background noise level of $L_p(A) < 5 \text{ dB(A)}$
 For further measurement conditions see chapter aerodynamics.

a.) Operation condition:

5.000 1/min at free air flow

Optimal operating point	170,0 m ³ /h @ 81 Pa	
Sound power level at the optimal operating point	6,4 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	55,0 dB(A)	

4 Environment
4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	70 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic Requirements

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Dust requirements	None	
Salt fog requirements	None	

Permitted application area:

The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)

There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.

Please require severity levels and specification parameters from the responsible development departments.

Product Data Sheet
9693530215
 VWC0119AUGBS
 4414/2HH

5 Safety
5.1 Electrical Safety


Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	500 VAC / 1 Min. 850 VDC / 1 Sec.	
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Clearance / creepage distance	1,0 mm / 1,2 mm	
Protection class	III	

5.2 Approval Tests

CE	EC Declaration of Conformity	Yes
EAC	Eurasian Conformity	Yes
UL	Underwriters Laboratories	Yes / UL507, Electric Fans E38324
VDE	Association for Electrical, Electronic and Information Technologies	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment
CSA	Canadian Standards Association	Yes / C22.2 No. 113 Fans and Ventilators
CCC	China Compulsory Certification	Not applicable

6 Reliability
6.1 General

Life expectancy L10 at TU = 40 °C	50.000 h	
Life expectancy L10 at TU max.	25.000 h	
Life expectancy L10 acc. to IPC 9591 at TU = 40 °C	85.000 h	



Zeichnung entspricht 3D-Modell:
Drawing is equivalent to 3D-Model:
9293510500 CPA 000_A

ISO Status Data	ANSI - Nr. / Change No.	DATA System Version/ DATA System Version	DATA Name	QAD-Information/ QAD-Information	Material / Material: Volume (per 30): Weight / Mass (g/m):
			Shape / Form	Notes	
Tolerierung / Tolerances:			Def. of Profile	Article / Title:	
			Radius		
Allgemeintoleranzen / Gen. Tolerances:			30g.-Nr. / Drawing No:		
			First, 2ndg. / 1st/2ndg:		
ebm-papst St. Georgen GmbH & Co KG			Document type of Document	Index / Index	Format / Sizes: Maximal/Scale 2:1

- 1.) Maße fuer Montageausschnitt
- max. Anziehdrehmoment = 0,8Nm
 - Axialspiel: mit Feder spielfrei verspannt
 - Anzahl und Länge der Litzen siehe BV- Bl. 1

- 1.) measures for mounting cut-out
- Ⓐ — - max. tightening torque = 0.8Nm
- without axial clearance by a pre-loaded spring
- length and number of wires see design specification page 1