

KARTA KATALOGOWA

4650 TA

Wentylator osiowy kompaktowy AC

Producent: ebm-papst

**Dane znamionowe**

Napięcie znamionowe	230 V AC
Częstotliwość	50 Hz
Prędkość obrotowa	2550 obr/min
Pobór mocy	19,0 W
Wydajność	138 m³/h
Poziom ciśnienia akustycznego	41 dB(A)
Temperatura otoczenia	-10...+45 °C

Budowa

Wymiary	Ø 113 × 37 mm
Materiał wirnika	metal
Kierunek obrotów	w prawo, patrząc na wirnik
Zabezpieczenie silnika	impedancyjne (odporny na przeciążenie)
Łożyskowanie	ślizgowe Sintec
Trwałość L10 (40 °C)	37500 h
Masa	0,430 kg


Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
Producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

4650 TA

AC axial compact fan


ebm-papst St. Georgen GmbH & Co. KG

Hermann-Papst-Straße 1

D-78112 St. Georgen

Phone +49 7724 81-0

Fax +49 7724 81-1309

info2@de.ebmpapst.com

www.ebmpapst.com

Nominal data

Type	4650 TA	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Speed	min ⁻¹	2550
Power input	W	19.0
Min. ambient temperature	°C	-10
Max. ambient temperature	°C	45
Air flow	m ³ /h	138
Sound pressure level	dB(A)	41

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations



4650 TA

AC axial compact fan

Technical features

Dimensions	113 Ø x 37 mm
General description	AC voltage fan with external rotor shaded-pole motor. Protected from overload by impedance protection. Impeller and mounting bracket made of metal. Inlet via mounting bracket. Rotational direction clockwise looking at rotor. Electrical connection to 2 single strands. Strand ends bared and tin-plated. Mass 430 g. Please note our new ACmaxx series. With identical fastening dimensions and voltages, this series achieves higher energy efficiency.
Connection line	2 single strands AWG 22, TR 32
Direction of rotation	Right, looking at rotor
Direction of air flow	Inlet via mounting bracket.
Bearing	Sintec sleeve bearing system
Lifetime L10 at 40 °C	37500 h
Lifetime L10 at maximum temperature	32500 h
Mass	0.430 kg
Material of impeller	Metal
Motor protection	Protected from overload using impedance protection
Approval	VDE, CSA, UL, CE

4650 TA

AC axial compact fan

Product drawing

