KARTA KATALOGOWA

632/2HPU

Wentylator osiowy DC

Producent: ebm-papst

Dane znamionowe	
Napięcie znamionowe	**12 V DC (10,8…13,2 V DC)**
Prędkość obrotowa	**6400 obr/min**
Pobór mocy	**1,5 W**
Wydajność	**44 m³/h**
Maks. ciśnienie statyczne	**114 Pa**
Poziom ciśnienia akustycznego	**35 dB(A)**
Poziom mocy akustycznej	**5,4 B**
Temperatura otoczenia	**−20…+70 °C**

Budowa	
Wymiary	**60 × 60 × 25 mm**
Trwałość L10 (40 °C)	**85000 h**
Masa	**0,07 kg**

Charakterystyka przepływowa

Charts



Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
Producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

632 /2HPU

DC axial fan

ebm-papst St. Georgen GmbH & Co. KG
Hermann-Papst-Straße 1
D-78112 St. Georgen
Phone +49 7724 81-0
Fax +49 7724 81-1309
info2@de.ebmpapst.com
www.ebmpapst.com

Nominal data

Type	632 /2HPU	
Nominal voltage	VDC	12
Nominal voltage range	VDC	10,8 .. 13,2
Speed	min^{-1}	6400
Power input	W	1.5
Min. ambient temperature	°C	-20
Max. ambient temperature	°C	70
Air flow	m^3/h	44
Sound power level	B	5.4
Sound pressure level	dB(A)	35

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

632 /2HPU

DC axial fan

Technical features

General description	Particular design features: Rigid compression curve for high air flow at high counterpressure. Motor has very low structure-borne noise. Control inputs and alarm and speed signals available on request. Developed for applications with stringent environmental requirements. General features: Material: fibreglass-reinforced plastic. Impeller PA, housing PBT. Electronic commutation completely integrated. Protected against reverse polarity and locking. Connection via single strands AWG 22, TR 64, bared and tin-plated. Air exhaust over bars. Rotational direction clockwise looking at rotor. Mass: 70 g.
Mass	0.07 kg
Dimensions	60 x 60 x 25 mm
Lifetime L10 at 40 °C	85000 h
Lifetime L10 at maximum temperature	42500 h

ebm-papst St. Georgen GmbH & Co. KG · Hermann-Papst-Straße 1 · D-78112 St. Georgen · Phone +49 7724 81-0 · Fax +49 7724 81-1309 · info2@de.ebmpapst.com · www.ebmpapst.com

632 /2HPU

DC axial fan

Product drawing



ebm-papst St. Georgen GmbH & Co. KG · Hermann-Papst-Straße 1 · D-78112 St. Georgen · Phone +49 7724 81-0 · Fax +49 7724 81-1309 · info2@de.ebmpapst.com · www.ebmpapst.com

632 /2HPU

DC axial fan

Charts



ebm-papst St. Georgen GmbH & Co. KG · Hermann-Papst-Straße 1 · D-78112 St. Georgen · Phone +49 7724 81-0 · Fax +49 7724 81-1309 · info2@de.ebmpapst.com · www.ebmpapst.com