

## KARTA KATALOGOWA

# 8300100096

Moduł promieniowy EC RadiPac, łopatki zakrzywione do tyłu, jednostronnie ssący (typ VBS0560CTTPS)

Producent: ebm-papst



Zdjęcie poglądowe


| Dane znamionowe           |                        |
|---------------------------|------------------------|
| Napięcie znamionowe       | 3~ 400 V (380...480 V) |
| Częstotliwość             | 50/60 Hz               |
| Prędkość obrotowa         | 2080 obr/min           |
| Pobór mocy                | 4400 W                 |
| Pobór prądu               | 6,7 A                  |
| Maks. wydajność           | 17900 m³/h             |
| Maks. ciśnienie statyczne | 1510 Pa                |
| Temperatura otoczenia     | -40...+40 °C           |

| Dane ErP (UE 327/2011)     |                             |
|----------------------------|-----------------------------|
| Sprawność całkowita        | 74,6 %                      |
| Przepływ w pkt. optymalnym | 12210 m³/h                  |
| Przyrost ciśnienia         | 926 Pa                      |
| Regulacja obrotów          | tak (0-10 V / PWM / MODBUS) |

| Budowa           |             |
|------------------|-------------|
| Średnica wirnika | 560 mm      |
| Materiał wirnika | tworzywo PP |
| Liczba łopatek   | 5           |
| Stopień ochrony  | IP55        |
| Klasa izolacji   | F           |
| Masa             | 26,22 kg    |

## Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-215087-1  
Date: 2021-07-26  
Nozzle: 8217101924

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).

Wartości znamionowe dla punktu maksymalnego obciążenia; producent zastrzega możliwość zmian.

## Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199  
biuro@luftberg.pl · www.luftberg.pl

8300100096  
VBS0560CTTPS

# EC centrifugal fan - RadiPac

backward-curved, single-intake

**ebm-papst Mulfingen GmbH & Co. KGaA & Co. KG**  
Bachmühle 2 · D-74673 Mulfingen  
Phone +49 7938 81-0  
info1@de.ebmpapst.com  
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen  
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen  
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

|                          |                   |            |
|--------------------------|-------------------|------------|
| Item                     | 8300100096        |            |
| Motor                    | E15031-85         |            |
| Phase                    |                   | 3~         |
| Nominal voltage          | VAC               | 400        |
| Nominal voltage range    | VAC               | 380 .. 480 |
| Frequency                | Hz                | 50/60      |
| Method of obtaining data |                   | ml         |
| Speed (rpm)              | min <sup>-1</sup> | 2080       |
| Power consumption        | W                 | 4400       |
| Current draw             | A                 | 6.7        |
| Min. ambient temperature | °C                | -40        |
| Max. ambient temperature | °C                | 40         |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

## Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

|                                   |   | Actual | Req. 2015 |                               |                   |       |
|-----------------------------------|---|--------|-----------|-------------------------------|-------------------|-------|
| 01 Overall efficiency $\eta_{es}$ | % | 74.6   | 58.2      | 09 Power consumption $P_{ed}$ | kW                | 4.36  |
| 02 Measurement category           |   | A      |           | 09 Air flow $q_v$             | m³/h              | 12210 |
| 03 Efficiency category            |   | Static |           | 09 Pressure increase $p_{fs}$ | Pa                | 926   |
| 04 Efficiency grade N             |   | 78.4   | 62        | 10 Speed (rpm) n              | min <sup>-1</sup> | 2080  |
| 05 Variable speed drive           |   | Yes    |           | 11 Specific ratio*            |                   | 1.01  |

Data obtained at optimum efficiency level.

\* Specific ratio =  $1 + p_{fs} / 100\,000\text{ Pa}$

LU-215087

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).  
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.

The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

8300100096  
VBS0560CTTPS

## EC centrifugal fan - RadiPac

backward-curved, single-intake

### Technical description

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight                                                                     | 26.22 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Size                                                                       | 560 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Motor size                                                                 | 150                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Rotor surface                                                              | Painted black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Electronics housing material                                               | Die-cast aluminum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Impeller material                                                          | PP plastic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Number of blades                                                           | 5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Direction of rotation                                                      | Clockwise, viewed toward rotor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Degree of protection                                                       | IP55                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Insulation class                                                           | "F"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Moisture (F) / Environmental (H) protection class                          | H1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Ambient temperature note                                                   | Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.                                                                                                                                                                                                                                                                                                                                                                                                          |
| Max. permitted ambient temp. for motor (transport/storage)                 | +80 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Min. permitted ambient temp. for motor (transport/storage)                 | -40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Condensation drainage holes                                                | On rotor side                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Mode                                                                       | S1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Motor bearing                                                              | Ball bearing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Technical features                                                         | <ul style="list-style-type: none"> <li>- Operation and alarm display with LED</li> <li>- External 15-50 VDC input (parameterization)</li> <li>- Alarm relay</li> <li>- Integrated PI controller</li> <li>- Configurable inputs/outputs (I/O)</li> <li>- MODBUS V6.3</li> <li>- Motor current limitation</li> <li>- RS-485 MODBUS-RTU</li> <li>- Soft start</li> <li>- Voltage output 3.3-24 VDC, Pmax = 800 mW</li> <li>- Control interface with SELV potential safely disconnected from the mains</li> <li>- Thermal overload protection for electronics/motor</li> <li>- Line undervoltage / phase failure detection</li> <li>- Vibration sensor</li> </ul> |
| Power Factor Correction (PFC)                                              | Passive (through low-capacitance DC link)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| EMC immunity to interference                                               | According to EN 61000-6-2 (industrial environment)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| EMC interference emission                                                  | According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 3.5 mA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Electrical hookup                                                          | Terminal box                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Motor protection                                                           | Electronic motor protection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Protection class assignment                                                | I; If a protective earth is connected.<br>The built-in component has several local protection class assignments.<br>The final protection class is determined by the intended installation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

8300100096  
VBS0560CTTPS

EC centrifugal fan - RadiPac  
backward-curved, single-intake


|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Conformity with standards | EN 61800-5-1; CE; UKCA                                        |
| Approval                  | EAC; CSA C22.2 No. 77 + CAN/CSA-E60730-1; UL 1004-7 + 60730-1 |

8300100096  
VBS0560CTTPS

## EC centrifugal fan - RadiPac

backward-curved, single-intake

### Product drawing




|   |                                                                                                                                                                                                                   |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Accessory part: Inlet ring 8217102237 with pressure tap (k-factor: 381) (not included in scope of delivery)                                                                                                       |
| 2 | Max. clearance for screw 20 mm                                                                                                                                                                                    |
| 3 | Cable diameter min. 4 mm, max. 10 mm, tightening torque $4 \pm 0.6$ Nm<br>(The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted) |
| 4 | Tightening torque $1.5 \pm 0.2$ Nm                                                                                                                                                                                |

8300100096  
VBS0560CTTPS

# EC centrifugal fan - RadiPac

backward-curved, single-intake

## Accessory part




Inlet ring 8217102237 with pressure tap (k-factor: 381)

8300100096  
VBS0560CTTPS

# EC centrifugal fan - RadiPac

backward-curved, single-intake

## Connection diagram



| No. | Conn. | Designation | Function/assignment                                                                                                                                                                                                                                                                                                                             |
|-----|-------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|     | CON1  | L1, L2, L3  | Power supply, phase, see nameplate for voltage range                                                                                                                                                                                                                                                                                            |
|     | PE    | PE          | Protective earth                                                                                                                                                                                                                                                                                                                                |
|     | CON2  | RSA         | RS485 interface for MODBUS, RSA; SELV                                                                                                                                                                                                                                                                                                           |
|     | CON2  | RSB         | RS485 interface for MODBUS, RSB; SELV                                                                                                                                                                                                                                                                                                           |
|     | CON2  | GND         | Reference ground for control interface, SELV                                                                                                                                                                                                                                                                                                    |
|     | CON2  | IO1         | Function parameterizable (see "Optional interface functions" table)<br>Factory setting:<br>Digital input - high active, function: Disable input, SELV<br>- inactive: Pin open or applied voltage < 1.5 VDC<br>- active: applied voltage 3.5-50 VDC<br>Reset function: Triggering of error reset on change of state from "enabled" to "disabled" |
|     | CON2  | IO2         | Function parameterizable (see "Optional interface functions" table)<br>Factory setting:<br>Analog input 0-10 V/PWM, Ri=100 kΩ, function: Set value<br>Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV                                                                                                         |
|     | CON2  | IO3         | Function parameterizable (see "Optional interface functions" table)<br>Factory setting:<br>Analog output 0-10 V, max. 5 mA, function: Actual speed<br>Characteristic curve parametrizable (see output characteristic curve P3-OUT), SELV                                                                                                        |
|     | CON2  | Vout        | Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable<br>Factory setting: 10 VDC<br>short-circuit-proof, supply for external devices, SELV<br>alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage                                                                                                 |
|     | CON2  | COM         | Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side                                                                                                                                                                   |
|     | CON2  | NC          | Status relay, floating status contact, break for failure                                                                                                                                                                                                                                                                                        |
|     |       | LED         | green: status = good, ready for operation<br>orange: status = warning<br>red: status = failure                                                                                                                                                                                                                                                  |
|     |       | P1-IN       | Input characteristic curve                                                                                                                                                                                                                                                                                                                      |
|     |       | P3-OUT      | Output characteristic curve                                                                                                                                                                                                                                                                                                                     |

# EC centrifugal fan - RadiPac


## Terminal/plug assignment

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.3

8300100096  
VBS0560CTTPS

EC centrifugal fan - RadiPac  
backward-curved, single-intake

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-215087-1  
Date: 2021-07-26  
Nozzle: 8217101924

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|    | Wired | U   | f  | n                 | P <sub>e</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | LwA <sub>out</sub> | LwA | q <sub>v</sub> | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|----|-------|-----|----|-------------------|----------------|------|-------------------|-------------------|--------------------|-----|----------------|-----------------|----------------|-----------------|
|    |       | V   | Hz | min <sup>-1</sup> | W              | A    | dB(A)             | dB(A)             | dB(A)              | dB  | m³/h           | Pa              | cfm            | in. wg          |
| 1  | 3~    | 400 | 50 | 2080              | 2670           | 4.12 | 84                | 92                | 96                 | 98  | 17935          | 0               | 10555          | 0.00            |
| 2  | 3~    | 400 | 50 | 2080              | 3864           | 5.89 | 78                | 86                | 90                 | 92  | 15700          | 500             | 9240           | 2.01            |
| 3  | 3~    | 400 | 50 | 2080              | 4400           | 6.70 | 72                | 80                | 85                 | 87  | 11265          | 1000            | 6630           | 4.01            |
| 4  | 3~    | 400 | 50 | 2080              | 4112           | 6.27 | 77                | 84                | 89                 | 90  | 7060           | 1250            | 4155           | 5.02            |
| 5  | 3~    | 400 | 50 | 1735              | 1584           | 2.53 | 79                | 87                | 91                 | 92  | 15020          | 0               | 8840           | 0.00            |
| 6  | 3~    | 400 | 50 | 1735              | 2248           | 3.50 | 74                | 81                | 85                 | 87  | 13075          | 346             | 7695           | 1.39            |
| 7  | 3~    | 400 | 50 | 1735              | 2555           | 3.95 | 68                | 75                | 81                 | 82  | 9385           | 697             | 5525           | 2.80            |
| 8  | 3~    | 400 | 50 | 1735              | 2400           | 3.72 | 71                | 78                | 83                 | 84  | 5895           | 875             | 3470           | 3.51            |
| 9  | 3~    | 400 | 50 | 1300              | 734            | 1.34 | 72                | 80                | 84                 | 85  | 11320          | 0               | 6660           | 0.00            |
| 10 | 3~    | 400 | 50 | 1300              | 1004           | 1.71 | 66                | 74                | 78                 | 80  | 9790           | 194             | 5760           | 0.78            |
| 11 | 3~    | 400 | 50 | 1300              | 1124           | 1.87 | 60                | 68                | 74                 | 75  | 7015           | 389             | 4130           | 1.56            |
| 12 | 3~    | 400 | 50 | 1300              | 1062           | 1.79 | 62                | 70                | 75                 | 76  | 4415           | 492             | 2600           | 1.98            |
| 13 | 3~    | 400 | 50 | 865               | 263            | 0.67 | 62                | 70                | 74                 | 75  | 7530           | 0               | 4430           | 0.00            |
| 14 | 3~    | 400 | 50 | 865               | 331            | 0.79 | 57                | 65                | 69                 | 70  | 6425           | 84              | 3785           | 0.34            |
| 15 | 3~    | 400 | 50 | 865               | 366            | 0.84 | 51                | 59                | 63                 | 65  | 4645           | 171             | 2735           | 0.69            |
| 16 | 3~    | 400 | 50 | 865               | 352            | 0.82 | 50                | 57                | 62                 | 64  | 2940           | 218             | 1730           | 0.88            |

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
LwA<sub>out</sub> = Sound power level outlet side · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase