

KARTA KATALOGOWA

8300100759

Moduł promieniowy EC RadiPac, łopatki zakrzywione do tyłu, jednostronnie ssący (typ VBH0280CTPHS)

Producent: ebm-papst



Zdjęcie poglądowe


Dane znamionowe	
Napięcie znamionowe	3~ 400 V (380...480 V)
Częstotliwość	50/60 Hz
Prędkość obrotowa	4550 obr/min
Pobór mocy	1500 W
Pobór prądu	2,3 A
Maks. wydajność	4660 m³/h
Maks. ciśnienie statyczne	1650 Pa
Temperatura otoczenia	-40...+40 °C

Dane ErP (UE 327/2011)	
Sprawność całkowita	69,6 %
Przepływ w pkt. optymalnym	3075 m³/h
Przyrost ciśnienia	1145 Pa
Regulacja obrotów	tak (MODBUS)

Budowa	
Średnica wirnika	280 mm
Materiał wirnika	tworzywo PP
Liczba łopatek	5
Stopień ochrony	IP55
Klasa izolacji	F
Masa	10,74 kg

Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-225672-1
Date: 2023-02-23
Nozzle: 8217102502

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).

Wartości znamionowe dla punktu maksymalnego obciążenia; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

8300100759

VBH0280CTPHS

EC centrifugal module - RadiPac

backward-curved, single-intake

with support bracket

ebm-papst Mulfingen GmbH & Co. KGaA & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH & Co. KGaA · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100759	
Motor	E09004-40	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Status		prelim.
Speed (rpm)	min ⁻¹	4550
Power consumption	W	1500
Current draw	A	2.3
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment

Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual		Req. 2015	
01 Overall efficiency η_{es}	%	69.6		53.3	
02 Measurement category		A			
03 Efficiency category		Static			
04 Efficiency grade N		78.3	62		
05 Variable speed drive		Yes			
09 Power consumption P_{ed}	kW			1.5	
09 Air flow q_v	m³/h			3075	
09 Pressure increase p_{fs}	Pa			1145	
10 Speed (rpm) n	min ⁻¹			4550	
11 Specific ratio*				1.01	

Data obtained at optimum efficiency level.

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).

The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.

The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$

LU-225672

8300100759

VBH0280CTPHS

EC centrifugal module - RadiPac

backward-curved, single-intake

with support bracket

Technical description

Weight	10.74 kg
Size	280 mm
Motor size	90
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Support plate material	Sheet steel, galvanized
Support bracket material	Steel, painted black
Inlet nozzle material	ABS plastic
Number of blades	5
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1 = Moist – occasional or constantly high level of humidity
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	See legend on product drawing
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Operation and alarm display with LED - Locked-rotor detection - Speed control - External 15-30 VDC input (parameterization) - Alarm relay - Configurable inputs/outputs (I/O) - Power limiter - MODBUS - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Control interface with SELV potential safely disconnected from the mains - Temperature derating - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
Power Factor Correction (PFC)	Passive (through low-capacitance DC link)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Electronic motor protection
With cable	Lateral

8300100759
VBH0280CTPHS

EC centrifugal module - RadiPac
backward-curved, single-intake
with support bracket

Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 61800-5-1; UKCA; CE
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; UL 1004-7 + 60730-1

8300100759


VBH0280CTPHS

EC centrifugal module - RadiPac

backward-curved, single-intake

with support bracket

Product drawing




1	Installed position: shaft horizontal (install support struts only vertically as illustrated) or rotor on bottom; rotor on top on request
2	Supply line (PWR) PVC AWG18 6x wire-end ferrule
3	Control wire (CTRL) PVC AWG22 6x wire-end ferrule
4	Inlet ring with pressure tap (k-factor: 98)
5	Fastening holes for FlowGrid 20280-2-2957 (not included in scope of delivery) are provided and must be subsequently opened as required

8300100759
VBH0280CTPHS

EC centrifugal module - RadiPac

backward-curved, single-intake
with support bracket

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	PWR	PE	green/yellow	Protective earth
	PWR	L1, L2, L3	black 1-3	Power supply, phase, see nameplate for voltage range
	PWR	COM	orange	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	PWR	NC	orange	Status relay, floating status contact, break for failure
	CTRL	GND	blue	Reference ground for control interface, SELV
	CTRL	Vout	red	Voltage output 10 VDC +/-3%, I _{max} =10 mA Short-circuit-proof, power supply for external devices, SELV alternative: 15-30 VDC input for parameterization via MODBUS without line voltage
	CTRL	IO1	yellow	Factory setting: Analog input 0-10 V / PWM, R _i =100 kΩ, function: set value Characteristic curve parameterizable (see input characteristic curve "Input curve 1"), SELV Function parameterizable (see table Optional interface functions)
	CTRL	IO2	white	Factory setting: Open collector output, U _{max} =50 VDC, I _{max} =20 mA, function:Tacho output 1 pulse/revolution, SELV Function parameterizable (see table Optional interface functions)
	CTRL	RSA	gray	RS-485 interface for MODBUS RSA, SELV dielectric strength to MODBUS RSB +/-14 V, dielectric strength to GND +/-7 V
	CTRL	RSB	brown	RS-485 interface for MODBUS RSB, SELV dielectric strength to MODBUS RSA +/-14 V, dielectric strength to GND +/-7 V
		LED		green: status = good, ready for operation orange: status = warning red: status = failure

EC centrifugal module - RadiPac

backward-curved, single-intake
with support bracket

[illegible]

configurable IO functions: normal / inverse

Functions and parameter description

- configurable function
- *function to be activated via IO Mode*

MODBUS Register for IO mode configuration

Electrical specification

configurable IO mode

- | | |
|---|--|
| <ul style="list-style-type: none"> ◦ Dm1 (high active): digital input | active: applied voltage 3.5 – 50 VDC
not active: pin open or applied voltage < 1.5 VDC, SELV |
| <ul style="list-style-type: none"> ◦ Dm1 (low active): digital input | active: applied voltage < 1.5 VDC
not active: pin open or applied voltage 3.5 – 50 VDC, SELV |
| <ul style="list-style-type: none"> ◦ Ain1 0-10 V/PWM: analog input | Ri = 100 k Ω , characteristic curve parameterizable, $f_{\text{PWM}} = 1 \text{ k} - 10 \text{ kHz}$, SELV |
| <ul style="list-style-type: none"> ◦ Ain1 0-10 V/PWM (with pull up): analog input | Ri = 100 k Ω , characteristic curve parameterizable, $f_{\text{PWM}} = 1 \text{ k} - 10 \text{ kHz}$, SELV |
| <ul style="list-style-type: none"> ◦ Dm1 (active high): digital input | active: applied voltage 3.5 – 50 VDC
not active: pin open or applied voltage < 1.5 VDC, SELV |
| <ul style="list-style-type: none"> ◦ Ain1 0-10 V/PWM: analog input | Ri = 100 k Ω , characteristic curve parameterizable, $f_{\text{PWM}} = 1 \text{ k} - 10 \text{ kHz}$, SELV |
| <ul style="list-style-type: none"> ◦ Tach out (open collector) | Umax = 50 VDC, Imax = 20 mA, SELV |
| <ul style="list-style-type: none"> ◦ Diagnostics out (open collector) | Umax = 50 VDC, Imax = 20 mA, SELV |
| <ul style="list-style-type: none"> ◦ Alarm out (open collector) | Umax = 50 VDC, Imax = 20 mA, SELV |
| <ul style="list-style-type: none"> ◦ Autoreaddressing pulse output (open collector) | Umax = 50 VDC, Imax = 20 mA, SELV |
| <ul style="list-style-type: none"> ◦ DCI-output (open collector) | Umax = 50 VDC, Imax = 20 mA, SELV |

102

- **Lach out** (open collector)
- **Diagnostics out** (open collector)
- **Alarm out** (open collector)
- **Autoaddressing pulse output** (open collector)
- **DCI-output** (open collector)

RS485	RS485 bus connection

MODBUS RTU, parameter specification V7.2, SELV

Relay

250 VAC / 2 A (AC1)

Voltage output

Voltage 10 VDC, SELV

15 - 30 VDC

Alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage


8300100759
VBH0280CTPHS

EC centrifugal module - RadiPac

backward-curved, single-intake

with support bracket

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-225672-1
Date: 2023-02-23
Nozzle: 8217102502

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	LwA	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	dB	m³/h	Pa	cfm	in. wg
1	3~	400	50	4550	1051	1.64	82	91	95	96	4660	0	2740	0.00
2	3~	400	50	4550	1360	2.11	76	84	91	92	4090	600	2405	2.41
3	3~	400	50	4550	1500	2.30	72	80	88	88	3035	1150	1785	4.62
4	3~	400	50	4550	1423	2.20	80	87	94	95	1980	1450	1165	5.82
5	3~	400	50	4140	785	1.26	80	88	93	94	4225	0	2485	0.00
6	3~	400	50	4140	1039	1.65	74	82	88	89	3710	493	2180	1.98
7	3~	400	50	4140	1146	1.81	70	77	85	86	2760	959	1625	3.85
8	3~	400	50	4140	1090	1.73	77	85	91	92	1805	1200	1060	4.82
9	3~	400	50	3220	393	0.68	73	82	86	87	3285	0	1935	0.00
10	3~	400	50	3220	507	0.84	68	76	83	84	2865	295	1685	1.18
11	3~	400	50	3220	562	0.93	65	72	81	82	2140	576	1260	2.31
12	3~	400	50	3220	535	0.89	69	77	84	85	1405	730	830	2.93
13	3~	400	50	2300	171	0.38	65	73	77	78	2365	0	1395	0.00
14	3~	400	50	2300	212	0.44	60	68	73	74	2035	149	1200	0.60
15	3~	400	50	2300	231	0.46	57	64	71	72	1525	293	900	1.18
16	3~	400	50	2300	223	0.45	61	67	73	74	1010	375	595	1.51

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase