


KARTA KATALOGOWA

D4E225-CC01-56

Wentylator promieniowy AC, łopatki zakrzywione do przodu, dwustronnie ssący, z obudową (z dużym kołnierzem)


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 230 V	Wielkość	225 mm
Częstotliwość	50 / 60 Hz	Silnik	M4E074-LA
Prędkość obrotowa	1210 / 1300 obr/min	Materiał wirnika	blacha stalowa ocynkowana
Pobór mocy	540 / 625 W	Obudowa	blacha stalowa ocynkowana
Pobór prądu	2,4 / 2,75 A	Kratka ochronna	stal powlekana tworzywem (RAL 9006)
Kondensator	16 µF / 400 V	Kierunek obrotów	w lewo, patrząc na wirnik
Temperatura otoczenia	-25...+30 °C	Stopień ochrony	IP22
		Klasa izolacji	B
		Zabezpieczenie silnika	termik (TOP), wyprowadzony, izolacja podstawowa
		Łożyskowanie	kulkowe, ze stali nierdzewnej
		Masa	12 kg

Charakterystyka przepływowa (50 Hz)

Charts: Air flow 50 Hz



Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
Wartości przy maksymalnym obciążeniu; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

D4E225-CC01-56

AC centrifugal fan

forward curved, dual inlet
with housing (large flange)

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Nominal data

Type	D4E225-CC01-56		
Motor	M4E074-LA		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50	60
Type of data definition		ml	ml
Valid for approval / standard		CE	CE
Speed (rpm)	min ⁻¹	1210	1300
Power input	W	540	625
Current draw	A	2.4	2.75
Motor capacitor	µF	16	16
Capacitor voltage	VDB	400	400
Capacitor standard		S2 (CE)	S2 (CE)
Min. back pressure	Pa	250	300
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	30	30

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data in accordance with ecodesign regulation EU 327/2011

		Actual	Request 2015
01 Overall efficiency η_e	%	40.2	40.2
02 Measurement category		B	
03 Efficiency category		Total	
04 Efficiency grade N		49	49
05 Variable speed drive		No	

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

09 Power input P_e	kW	0.4
09 Air flow q_v	m³/h	1595
09 Pressure increase p_f	Pa	355
10 Speed (rpm) n	min ⁻¹	1345
11 Specific ratio*		1.00

* Specific ratio = $1 + p_f / 100\,000\text{ Pa}$

LU-135956



D4E225-CC01-56

AC centrifugal fan

forward curved, dual inlet
with housing (large flange)


Technical features

Mass	12 kg
Size	225 mm
Motor size	74
Material of impeller	Sheet steel, galvanised
Housing material	Sheet steel, galvanised
Material of guard grille	Steel, coated in white aluminium plastic (RAL 9006)
Motor suspension	Motor mounted anti-vibration on both sides
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP22
Insulation class	"B"
Humidity (F) / environmental protection class (H)	H0 - dry environment
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensation drainage holes	None, open rotor
Operation mode	S1
Motor bearing	Ball bearings made of stainless steel
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) brought out, basic insulation
Protection class	I (if protective earth is connected by customer)
Motor capacitor according to EN 60252-1 in safety protection class	S2
Product conforming to standard	EN 60335-1; CE
Approval	UL 1004-1; CCC; CSA C22.2 no. 100

D4E225-CC01-56

AC centrifugal fan
forward curved, dual inlet
with housing (large flange)

Product drawing




1	Capacitor	2	Z (brown)	3	L (blue)
4	TOP (grey)	5	PE (green/yellow)	6	TOP (grey)
7	Capacitor	8	N (black)		



D4E225-CC01-56

AC centrifugal fan
forward curved, dual inlet
with housing (large flange)

Connection screen



U1	Blue	Z	brown	U2	black
PE	green/yellow	TOP	2 x grey		




D4E225-CC01-56

AC centrifugal fan

forward curved, dual inlet

with housing (large flange)

Charts: Air flow 50 Hz



Measured values

	U	f	n	P _e	I	q _v	P _{fs}	q _v	P _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	230	50	1210	540	2.40	2210	250	1300	1.00
2	230	50	1300	459	2.04	1865	320	1100	1.28
3	230	50	1365	378	1.71	1445	360	850	1.45
4	230	50	1405	320	1.48	1005	370	590	1.49

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase




D4E225-CC01-56

AC centrifugal fan

forward curved, dual inlet
with housing (large flange)

Charts: Air flow 60 Hz



Measurement: LU-35316-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L_{WA} measured as per ISO 13347 / L_{pA} measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	230	60	1300	625	2.75	1995	300	1175	1.20
2	230	60	1465	553	2.43	1700	400	1000	1.61
3	230	60	1565	474	2.13	1340	450	790	1.81
4	230	60	1645	390	1.83	800	490	470	1.97

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

