

KARTA KATALOGOWA

G2E140-AL30-48

Wentylator promieniowy AC, łopatki zakrzywione do przodu, jednostronnie ssący, z obudową (z kołnierzem)


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 115 V	Wielkość	140 mm
Częstotliwość	60 Hz	Silnik	M2E068-CF
Prędkość obrotowa	1950 obr/min	Materiał wirnika	blacha stalowa ocynkowana
Pobór mocy	130 / 135 W	Obudowa	odlew aluminiowy
Pobór prądu	1,1 / 1,15 A	Kierunek obrotów	w prawo, patrząc na wirnik
Prąd rozruchowy	0,95 A	Stopień ochrony	IP44
Kondensator	10 µF / 220 V	Klasa izolacji	B
Maks. wydajność	265 m³/h	Zabezpieczenie silnika	termik (TOP), podłączony wewnętrznie
Maks. ciśnienie statyczne	430 Pa	Łożyskowanie	kulkowe
Temperatura otoczenia	-25...+40 °C	Masa	2,9 kg

Charakterystyka przepływowa (60 Hz)

Curves: Air performance 60 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-167465-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
Wartości przy maksymalnym obciążeniu; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

G2E140-AL30-48

AC centrifugal fan
forward-curved, single-intake
with housing (flange)



ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Nominal data

Type	G2E140-AL30-48		
Motor	M2E068-CF		
Phase		1~	1~
Nominal voltage	VAC	115	115
Frequency	Hz	60	60
Method of obtaining data		ml	ml
Valid for approval/standard		CE	UL 1004-3
Speed (rpm)	min ⁻¹	1950	1950
Power consumption	W	130	135
Current draw	A	1.1	1.15
Capacitor	µF	10	10
Capacitor voltage	VDB	220	220
Capacitor standard		S0 (CE)	UL
Min. back pressure	Pa	200	200
Min. back pressure	inH2O	0.8	0.8
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	40	40
Starting current	A	0.95	

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



G2E140-AL30-48

AC centrifugal fan

forward-curved, single-intake
with housing (flange)

Technical description


Weight	2.9 kg
Fan size	140 mm
Rotor surface	Unpainted
Impeller material	Sheet steel, galvanized
Housing material	Die-cast aluminum
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0 - dry environment
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	UL 2111; CSA C22.2 No. 113

G2E140-AL30-48

AC centrifugal fan


forward-curved, single-intake
with housing (flange)

Product drawing



- | | |
|---|-------------------------------------|
| 1 | Cable PVC AWG20, 4x crimped splices |
|---|-------------------------------------|

Connection diagram



U1	blue	Z	brown	U2	black
PE	green/yellow				


G2E140-AL30-48

AC centrifugal fan

forward-curved, single-intake

with housing (flange)

Curves: Air performance 60 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-167465-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	P _{fs}	q _v	P _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH2O
1	115	60	1980	130	1.10	265	200	155	0.80
2	115	60	2215	122	1.07	225	260	130	1.04
3	115	60	2420	121	1.05	175	300	105	1.20
4	115	60	2635	119	1.04	135	340	80	1.36

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

