

KARTA KATALOGOWA

G2E140-PI28-14

Wentylator promieniowy AC, łopatki zakrzywione do przodu, jednostronnie ssący, z obudową (z kołnierzem)

Producent: ebm-papst




Zdjęcie poglądowe

Dane znamionowe	
Napięcie znamionowe	1~ 230 V
Częstotliwość	50 / 60 Hz
Prędkość obrotowa	2120 / 2170 obr/min
Pobór mocy	185 / 205 W
Pobór prądu	0,8 / 0,89 A
Kondensator	4 µF / 400 V
Maks. wydajność	565 m³/h
Maks. ciśnienie statyczne	400 Pa
Temperatura otoczenia	min. -25 °C; maks. 60 / 35 °C

Budowa	
Wielkość	140 mm
Silnik	M2E068-DF
Materiał wirnika	blacha stalowa malowana na czarno
Obudowa	blacha stalowa ocynkowana
Kierunek obrotów	w prawo, patrząc na wirnik
Stopień ochrony	IP44
Klasa izolacji	B
Zabezpieczenie silnika	termik (TOP), podłączony wewnętrznie
Łożyskowanie	kulkowe
Masa	3,3 kg

Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
Wartości przy swobodnym wydmuchu; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

G2E140-PI28-14

AC centrifugal fan
forward-curved, single-intake
with housing (flange)

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Nominal data

Type	G2E140-PI28-14		
Motor	M2E068-DF		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50	60
Method of obtaining data		fa	fa
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	2120	2170
Power consumption	W	185	205
Current draw	A	0.8	0.89
Capacitor	µF	4	4
Capacitor voltage	VDB	400	400
Capacitor standard		S0 (CE)	S0 (CE)
Min. back pressure	Pa	0	0
Min. back pressure	inH2O	0	0
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	60	35

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



G2E140-PI28-14

AC centrifugal fan

forward-curved, single-intake
with housing (flange)

Technical description

Weight	3.3 kg
Fan size	140 mm
Rotor surface	Painted black
Impeller material	Sheet steel, painted black
Housing material	Sheet steel, galvanized
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent as per EN 60034-5
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0+
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Axial
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	CCC


G2E140-PI28-14

AC centrifugal fan

forward-curved, single-intake


with housing (flange)

Product drawing



1 Cable PVC 4G 0.5 mm², 4x crimped splices

Connection diagram




U1	blue	Z	brown	U2	black
PE	green/yellow				



G2E140-PI28-14

AC centrifugal fan
forward-curved, single-intake
with housing (flange)

Curves: Air performance 50 Hz



Measurement: LU-44743-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	Pe	I	qv	pfs	qv	pfs
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH2O
1	230	50	2120	185	0.80	565	0	335	0.00
2	230	50	2385	156	0.68	485	200	285	0.80
3	230	50	2550	133	0.58	400	340	235	1.36
4	230	50	2690	110	0.48	290	400	170	1.61

U = Power supply · f = Frequency · n = Speed (rpm) · Pe = Power consumption · I = Current draw · qv = Air flow · pfs = Pressure increase




G2E140-PI28-14

AC centrifugal fan

forward-curved, single-intake

with housing (flange)

Curves: Air performance 60 Hz



Measurement: LU-44744-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH2O
1	230	60	2170	205	0.89	510	0	300	0.00
2	230	60	2400	198	0.86	460	240	270	0.96
3	230	60	2870	169	0.75	360	460	210	1.85
4	230	60	3150	142	0.66	230	540	135	2.17

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

