

KARTA KATALOGOWA

G2E146-DW07-01

Dmuchawa promieniowa AC, łopatki zakrzywione do przodu, jednostronnie ssąca, w obudowie

Producent: ebm-papst




Zdjęcie poglądowe

Dane znamionowe	
Napięcie znamionowe	1~ 230 V
Częstotliwość	50/60 Hz
Prędkość obrotowa	1550 / 1750 obr/min
Pobór mocy	140 / 155 W
Pobór prądu	0,62 / 0,68 A
Kondensator	3 µF / 450 V
Maks. temp. otoczenia	+45 °C / +30 °C
Maks. wydajność	480 m³/h
Maks. ciśnienie statyczne	450 Pa

Budowa	
Wielkość	146 mm
Materiał wirnika	stal ocynkowana
Klasa izolacji	B
Zabezpieczenie silnika	termik (TOP)
Masa	2,9 kg

Charakterystyka przepływowa (50 Hz)

Charts: Air flow 50 Hz



Measurement: LU-105087

Air performance measured as per ISO 5801 Installation Category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

G2E146-DW07-01

AC centrifugal fan

forward curved, single inlet
with housing (flange)

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2
D-74673 Mulfingen
Phone: +49(0)7938/81-0
Fax: +49(0)7938/81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Nominal data

Type	G2E146-DW07-01				
Motor	M2E068-CA				
Phase		1~	1~	1~	1~
Nominal voltage	V	230	230	240	240
Frequency	Hz	50	60	50	60
Type of data definition		rfa	ml	ml	ml
Valid for approval / standard		CE	CE	CE	CE
Speed	min ⁻¹	1550	1750	1775	2150
Power input	W	140	155	130	140
Current draw	A	0.62	0.68	0.55	0.59
Motor capacitor	µF	3	3	2.5	2.5
Capacitor voltage	VDB	450	450	450	450
Capacitor standard		P0 (CE)	P0 (CE)	P0 (CE)	P0 (CE)
Min. back pressure	Pa	0	100	50	250
Max. ambient temperature	°C	45	30	45	45

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

G2E146-DW07-01

AC centrifugal fan

forward curved, single inlet
with housing (flange)

Technical features


Leackage current	< 0.75 mA
Size	146 mm
Operation mode	S1
Direction of rotation	Clockwise, seen on rotor
Mounting position	Any
Humidity class	F0
Insulation class	"B"
Condensate discharge holes	None
Motor bearing	Ball bearing
Mass	2.9 kg
Housing material	Die-cast aluminum
Material of impeller	Sheet steel, sendzimir galvanised
Motor protection	Thermal overload protector (TOP) wired internally
Product conforming to standard	CE; EN 60335-1
Surface of rotor	Partially cast in aluminium
Type of protection	IP 44; Depending on installation and position
Protection class	I
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Approval	CCC

G2E146-DW07-01

AC centrifugal fan


forward curved, single inlet
with housing (flange)

Product drawing



1 Connection line PVC, 4x brass lead tips crimped

Connection screen




U1	blue	Z	brown	U2	black
PE	green/yellow				

G2E146-DW07-01

AC centrifugal fan

forward curved, single inlet
with housing (flange)

Charts: Air flow 50 Hz



Measurement: LU-105087

Air performance measured as per ISO 5801 Installation Category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P ₁	I	qv	P _{sf}
	V	Hz	min ⁻¹	W	A	m³/h	Pa
1	230	50	1550	140	0.62	475	0
2	230	50	2035	122	0.53	380	200
3	230	50	2395	104	0.45	260	351
4	230	50	2605	91	0.40	130	399


G2E146-DW07-01

AC centrifugal fan

forward curved, single inlet

with housing (flange)

Charts: Air flow 60 Hz



Measurement: LU-105090

Air performance measured as per ISO 5801 Installation Category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P ₁	I	qv	P _{sf}
	V	Hz	min ⁻¹	W	A	m³/h	Pa
1	230	60	1750	155	0.68	380	97
2	230	60	2145	144	0.62	310	275
3	230	60	2500	137	0.59	235	376
4	230	60	2775	130	0.57	145	452