


KARTA KATALOGOWA

K2E200-AH08-15

Moduł wentylatora promieniowego AC, łopatki zakrzywione do tyłu, jednostronnie ssący, z obudową


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 115 V	Wielkość	200 mm
Częstotliwość	50 / 60 / 60 Hz	Silnik	M2E068-CF
Prędkość obrotowa	2650 / 3050 / 3100 obr/min	Materiał wirnika	tworzywo PA
Pobór mocy	75 / 90 / 93 W	Obudowa	tworzywo PP
Pobór prądu	0,78 / 0,80 / 0,79 A	Liczba łopatek	6
Prąd rozruchowy	1,67 / 1,56 / 1,56 A	Kierunek obrotów	w prawo, patrząc na wirnik
Kondensator	7 µF / 250 V	Stopień ochrony	IP44
Temperatura otoczenia	-30...+55 °C	Klasa izolacji	F
		Zabezpieczenie silnika	termik (TOP), podłączony wewnętrznie
		Łożyskowanie	kulkowe
		Masa	2,3 kg

Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



Measurement: LU-127588-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
Producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

K2E200-AH08-15

AC centrifugal module

backward-curved, single-intake

with housing

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Nominal data

Type	K2E200-AH08-15			
Motor	M2E068-CF			
Phase		1~	1~	1~
Nominal voltage	VAC	115	115	115
Frequency	Hz	50	60	60
Method of obtaining data		ce	ce	ce
Valid for approval/standard		CE	CE	UL 2111
Speed (rpm)	min ⁻¹	2650	3050	3100
Power consumption	W	75	90	93
Current draw	A	0.78	0.80	0.79
Capacitor	µF	7	7	7
Capacitor voltage	VDB	250	250	250
Capacitor standard		S0 (CE)	S0 (CE)	UL
Min. back pressure	Pa	0	0	0
Min. back pressure	inH2O	0	0	0
Min. ambient temperature	°C	-30	-30	-30
Max. ambient temperature	°C	55	55	55
Starting current	A	1.67	1.56	1.56

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment

Subject to change



K2E200-AH08-15

AC centrifugal module

 backward-curved, single-intake
with housing

Technical description


Weight	2.3 kg
Fan size	200 mm
Rotor surface	Unpainted
Impeller material	PA plastic
Housing material	PP plastic
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H0+
Max. permitted ambient temp. for motor (transport/storage)	+ 70 °C
Min. permitted ambient temp. for motor (transport/storage)	- 25 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Motor capacitor according to EN 60252-1 in safety protection class	S0
Conformity with standards	EN 60335-1; CE
Approval	UL 2111; CSA C22.2 No. 77

K2E200-AH08-15

AC centrifugal module


backward-curved, single-intake
with housing

Product drawing



1 Terminal strip Adels Contact LK 980-01 RZ/ 3 B V0

Connection diagram



L blue


N black

PE green/yellow

K2E200-AH08-15

AC centrifugal module
backward-curved, single-intake
with housing

Curves: Air performance 50 Hz



Measurement: LU-127588-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	q _v	P _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	cfm	inH2O
1	115	50	2650	75	0.78	460	270	0.00

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow




K2E200-AH08-15

AC centrifugal module

backward-curved, single-intake

with housing

Curves: Air performance 60 Hz



Measurement: LU-127589-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	q _v	P _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	cfm	inH ₂ O
1	115	60	3050	90	0.80	535	315	0.00

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow

