


Research Data

Air-flow rate[m ³ /h]	3825
Pressure[Pa]	369
Pressure Type	Psta
Power supply	all
Density[m ³ /h]	1.205

Label

Code	PC566
Voltage[V]	400
Phases	3
Current[A]	
Poles	6
Weight[kg]	87
Frequency[Hz]	50
Speed[rpm]	900
Power[kW]	2.2
IP	55
INS	



PMM-Q566

PP welded housing - PP/INOX impeller - epoxy painted motor support - stainless steel screws

Certificazioni







Table engines



Class IE	IE1	IE2	IE3
Size	112M	112M	112M
Power[kW]	2.2	2.2	2.2
Current[A]	5.43	5.18	5.3
Voltage[V]	400	400	400
Cos φ	0.76	0.75	0.72
n	0.77	0.818	0.843

Working point

Q [m ³ /h]	3825
P _{sta} [Pa]	369.0
P _{tot} [Pa]	403.0
P _{in} [kW] [W]	723.5
n _{sta}	0.541
n _{tot}	0.591
Rpm	900




Dimensions




A	B	C	D	E	F	G	H	I	L	N	Ø	P	R
416	560	80	400	330	388	50	710	445	330	289	14	270	325
S	T	U	V	X	X1	X2	Y	Z					
310	355	728	50	25	40	15	18	460					

Configurations & cad


LG 0°




LG 45°




LG 90°




LG 135°




LG 180°




LG 225°




LG 270°




LG 315°




RD 0°




RD 45°




RD 90°




RD 135°




RD 180°



RD 225°



RD 270°



RD 315°

