


Research Data

Air-flow rate[m ³ /h]	60000
Pressure[Pa]	1429
Pressure Type	Psta
Power supply	all
Density[m ³ /h]	1.205

Label

Code	PR1358
Voltage[V]	400
Phases	3
Current[A]	
Poles	8
Weight[kg]	1510
Frequency[Hz]	50
Speed[rpm]	750
Power[kW]	45
IP	55
INS	



PRL-Q1358

PP welded housing - INOX/Fe+ebonite impeller - epoxy painted motor support - stainless steel screws

Certificazioni








Table engines


Class IE	IE1
Size	280M
Power[kW]	45
Current[A]	89.4
Voltage[V]	400
Cos φ	0.79
n	0.92

Working point

Q [m³/h]	60000
P_{sta} [Pa]	1429.
P_{tot} [Pa]	1570.
P_{in} [kW] [W]	31639
n_{sta}	0.753
n_{tot}	0.829
Rpm	750


















Dimensions



A	B	C	D	E	F	G	H	H1	I	L	N	Ø	P
1020	1350	150	1350	1080	875	125	1700	1350	1120	800	1450	24	760
Q	R	S	T	U	V	X	X1	X2	Y	Z			
60	1528	1000	1140	1978	80	40	60	30	40	1100			

Configurations & cad

LG 0°

LG 45°

LG 90°

LG 135°

LG 180°

LG 225°

LG 270°

LG 315°

RD 0°

RD 45°

RD 90°

RD 135°

RD 180°

RD 225°

RD 270°

RD 315°
