

KARTA KATALOGOWA

R2D180-AL02-15

Wentylator promieniowy AC, łopatki zakrzywione do tyłu, jednostronnie ssący

Producent: ebm-papst




Zdjęcie poglądowe

Dane znamionowe		Budowa	
Napięcie znamionowe	3~ 400 V	Średnica wirnika	180 mm
Częstotliwość	50 Hz	Materiał wirnika	tworzywo PA
Prędkość obrotowa	2600 obr/min	Liczba łopatek	16
Pobór mocy	85 W	Stopień ochrony	IP44
Pobór prądu	0,17 A	Klasa izolacji	B
Maks. wydajność	695 m³/h	Zabezpieczenie silnika	termik (TOP)
Maks. ciśnienie statyczne	210 Pa	Masa	1,73 kg
Temperatura otoczenia	-25...+35 °C		

Charakterystyka przepływowa

Curves: Air performance 50 Hz



Measurement: LU-122345-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).

Wartości znamionowe dla punktu maksymalnego obciążenia; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

 tel. +48 600 100 371 · tel. +48 604 959 199
 biuro@luftberg.pl · www.luftberg.pl

R2D180-AL02-15

AC centrifugal fan

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	R2D180-AL02-15	
Motor	M2D068-CF	
Phase		3~
Nominal voltage	VAC	400
Wiring		Y
Frequency	Hz	50
Method of obtaining data		fa
Valid for approval/standard		CE
Speed (rpm)	min ⁻¹	2600
Power consumption	W	85
Current draw	A	0.17
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	35

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



R2D180-AL02-15

AC centrifugal fan

backward-curved, single-intake

Technical description

Weight	1.73 kg
Size	180 mm
Motor size	68
Rotor surface	Unpainted
Impeller material	PA plastic, glass-fiber reinforced
Number of blades	16
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Conformity with standards	CE
Approval	UL 1004-1; CSA C22.2 No. 100




R2D180-AL02-15

AC centrifugal fan

backward-curved, single-intake

Product drawing




- | | |
|---|---|
| 1 | Cable AWG20 -300 V, 6x crimped splices |
| 2 | Accessory part: inlet ring 09576-2-4013 not included in scope of delivery |
| 3 | Max. clearance for screw 5 mm |

R2D180-AL02-15

AC centrifugal fan

backward-curved, single-intake

Connection diagram




Y	Star connection	L1	= U1 = black	L2	= V1 = blue
L3	= W1 = brown	TOP	2x yellow	PE	green/yellow



R2D180-AL02-15

AC centrifugal fan
backward-curved, single-intake

Curves: Air performance 50 Hz



Measurement: LU-122345-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	Y	400	50	2600	85	0.17	695	0	410	0.00
2	Y	400	50	2570	89	0.17	595	80	350	0.32
3	Y	400	50	2570	88	0.17	485	150	285	0.60
4	Y	400	50	2650	75	0.16	330	210	195	0.84

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

