

KARTA KATALOGOWA

R2E085-AA01-05

Wentylator promieniowy AC, łopatki zakrzywione do przodu, jednostronnie ssący


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 230 V	Średnica wirnika	85 mm
Częstotliwość	50/60 Hz	Materiał wirnika	stal ocynkowana
Prędkość obrotowa	2350 / 2800 obr/min	Stopień ochrony	IP44
Pobór mocy	32 / 30 W	Klasa izolacji	B
Pobór prądu	0,15 / 0,14 A	Zabezpieczenie silnika	termik (TOP)
Kondensator	1 µF / 400 V	Masa	0,7 kg
Wydajność (swobodny wypływ)	80 / 95 m³/h		
Maks. ciśnienie statyczne	110 Pa		
Maks. temp. otoczenia	+50 °C (50 Hz) / +70 °C (60 Hz)		

Charakterystyka przepływowa

Charts: Air flow 50 Hz



Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).
Wartości dla 50 Hz / 60 Hz; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R2E085-AA01-05

AC centrifugal fan

forward curved, single inlet


ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2

74673 Mulfingen

Phone: +49 7938 81-0

Fax: +49 7938 81-110

www.ebmpapst.com
info1@de.ebmpapst.com

Nominal data

Type	R2E085-AA01-05		
Motor	M2E042-CA		
Phase		1~	1~
Nominal voltage	[V]	230	230
Frequency	[Hz]	50	60
Type of data definition		rfa	rfa
Valid for approval / standard		CE	CE
Speed	[min ⁻¹]	2350	2800
Power input	[W]	32	30
Current draw	[A]	0,15	0.14
Motor capacitor	[µF]	1	1
Capacitor voltage	[VDB]	400	400
Capacitor standard		P2 (CE)	P2 (CE)
Min. back pressure	[Pa]	0	0
Max. ambient temperature	[°C]	50	70
Air flow	[m ³ /h]	80	95
Back pressure	[Pa]	0	0
Sound pressure level	[dB(A)]	53	57

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

R2E085-AA01-05

AC centrifugal fan

forward curved, single inlet

Technical features


Size	85 mm
Operation mode	Continuous operation (S1)
Direction of rotation	Clockwise, seen on rotor
Insulation class	"B"
Cable exit	Axial
Bearing motor	Ball bearing
Mass	0.7 kg
Material of electronics housing	Rotor: Partially cast in aluminum
Material of impeller	Sendzimir galvanized sheet steel
Motor protection	Thermal overload protector (TOP) wired internally
Product conforming to standard	CE
Type of protection	IP 44 - depending on position
Protection class	I
Approval	CCC

R2E085-AA01-05

AC centrifugal fan

forward curved, single inlet

Product drawing




R2E085-AA01-05

AC centrifugal fan

forward curved, single inlet


Connection screen



R2E085-AA01-05

AC centrifugal fan
forward curved, single inlet

Charts: Air flow 50 Hz



Measured values

	f	n	P ₁	I
	[Hz]	[min ⁻¹]	[W]	[A]
1	50	2430	32	0.15
2	50	2590	30	0.14

R2E085-AA01-05

AC centrifugal fan
forward curved, single inlet

Charts: Air flow 60 Hz

