

KARTA KATALOGOWA

R2E140-AI28-05

Wentylator promieniowy AC, łopatki zakrzywione do przodu, jednostronnie ssący


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 230 V	Średnica wirnika	140 mm
Częstotliwość	50/60 Hz	Materiał wirnika	stal ocynkowana
Prędkość obrotowa	2400 / 2350 obr/min	Stopień ochrony	IP44
Pobór mocy	160 / 205 W	Klasa izolacji	B
Pobór prądu	0,7 / 0,9 A	Zabezpieczenie silnika	termik (TOP)
Kondensator	4 µF / 400 V	Masa	2,1 kg
Wydajność (swobodny wypływ)	485 / 480 m³/h		
Maks. ciśnienie statyczne	385 Pa		
Maks. temp. otoczenia	+70 °C (50 Hz) / +45 °C (60 Hz)		

Charakterystyka przepływowa

Charts: Air flow 50 Hz



Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).
Wartości dla 50 Hz / 60 Hz; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R2E140-AI28-05

AC centrifugal fan

forward curved, single inlet


ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2

74673 Mulfingen

Phone: +49 7938 81-0

Fax: +49 7938 81-110

www.ebmpapst.com
info1@de.ebmpapst.com

Nominal data

Type	R2E140-AI28-05			
Motor	M2E068-DF			
Phase		1~	1~	1~
Nominal voltage	[V]	230	230	230
Frequency	[Hz]	50	60	60
Type of data definition		rfa	rfa	rfa
Valid for approval / standard		CE	CE	UL 2111
Speed	[min ⁻¹]	2400	2350	2350
Power input	[W]	160	205	220
Current draw	[A]	0,7	0.9	0.96
Motor capacitor	[µF]	4	4	4
Capacitor voltage	[VDB]	400	400	400
Min. back pressure	[Pa]	0	0	0
Max. ambient temperature	[°C]	70	45	45
Air flow	[m ³ /h]	485	480	480
Back pressure	[Pa]	0	0	0
Sound pressure level	[dB(A)]	72	71	71

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

R2E140-AI28-05

AC centrifugal fan

forward curved, single inlet

Technical features


Size	140 mm
Operation mode	Continuous operation (S1)
Direction of rotation	Clockwise, seen on rotor
Insulation class	"B"
Cable exit	Variable
Bearing motor	Ball bearing
Mass	2.1 kg
Material of electronics housing	Rotor: Partially cast in aluminum
Material of impeller	Sendzimir galvanized sheet steel
Motor protection	Thermal overload protector (TOP) wired internally
Product conforming to standard	CE
Type of protection	IP 44 - depending on position
Protection class	I
Approval	CCC; GOST

R2E140-AI28-05

AC centrifugal fan

forward curved, single inlet

Product drawing




R2E140-AI28-05

AC centrifugal fan
forward curved, single inlet

Copyright (c) by Foxit Software
For Evaluation Only.


Connection screen



R2E140-AI28-05

AC centrifugal fan
forward curved, single inlet

Charts: Air flow 50 Hz



Measured values

	n	P ₁	I
	[min ⁻¹]	[W]	[A]
1	2485	148	0.65
2	2630	128	0.57

R2E140-AI28-05

AC centrifugal fan
forward curved, single inlet

Charts: Air flow 60 Hz

