

KARTA KATALOGOWA

R2E180-CR82-10

Wentylator promieniowy AC, jednostronnie ssący

Producent: ebm-papst




Zdjęcie poglądowe

Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 230 V	Średnica wirnika	180 mm
Częstotliwość	50 Hz	Materiał wirnika	stal ocynkowana
Prędkość obrotowa	2650 obr/min	Liczba łopatek	6
Pobór mocy	67 W	Stopień ochrony	IP44
Pobór prądu	0,3 A	Klasa izolacji	F
Kondensator	3 µF / 400 V	Zabezpieczenie silnika	termik (TOP)
Maks. wydajność	405 m³/h	Masa	2,8 kg
Maks. ciśnienie statyczne	260 Pa		
Temperatura otoczenia	-25...+80 °C		

Charakterystyka przepływowa

Charts: Air flow 50 Hz



Measurement: LU-116924

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).
Wartości dla 50 Hz / 60 Hz; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R2E180-CR82-10

AC hot-air circulation blower

for solid fuel heating systems

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

County court Stuttgart · HRB 590142

Nominal data

Type	R2E180-CR82-10	
Motor	M2E068-CF	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Type of data definition		cs
Valid for approval / standard		CE
Speed	min ⁻¹	2650
Power input	W	67
Current draw	A	0.30
Motor capacitor	µF	3
Capacitor voltage	VDB	400
Capacitor standard		P0 (CE)
Min. back pressure	Pa	0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	80

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations



R2E180-CR82-10

AC hot-air circulation blower

for solid fuel heating systems

Technical features


Mass	2.8 kg
Size	180 mm
Surface of rotor	Partially cast in aluminium
Material of impeller	Sheet steel, galvanised
Number of blades	6
Motor suspension	Motor anti-vibration mounted on one side via mounting plate
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 44; Depending on installation and position
Insulation class	"F"
Humidity class	F0
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	< 0.75 mA
Electrical leads	With plug
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60335-1; CE

R2E180-CR82-10

AC hot-air circulation blower

for solid fuel heating systems

Product drawing




1	Connection line silicone 4G 0.5 mm ² , Wieland connector shell 93.932.4853.0
1.1	black + capacitor
1.2	green / yellow
1.3	Blue

R2E180-CR82-10

AC hot-air circulation blower

for solid fuel heating systems

Connection screen



U1	blue	Z	brown	U2	black
PE	green/yellow				




R2E180-CR82-10

AC hot-air circulation blower

for solid fuel heating systems

Charts: Air flow 50 Hz



Measurement: LU-116924

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P _e	I	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa
1	230	50	2650	67	0.30	405	0
2	230	50	2660	66	0.29	330	120
3	230	50	2720	62	0.27	240	220
4	230	50	2760	58	0.25	170	260

U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · qv = Air flow · p_{fs} = Pressure increase