

## KARTA KATALOGOWA

# R2E250-RB06-19

Wentylator promieniowy AC RadiCal, łopatki zakrzywione do tyłu, jednostronnie ssący

Producent: ebm-papst



## Dane znamionowe

|                           |                                    |
|---------------------------|------------------------------------|
| Napięcie znamionowe       | 1~ 230 V                           |
| Częstotliwość             | 50 / 60 / 60 Hz                    |
| Prędkość obrotowa         | 2750 / 3100 / 3100 obr/min         |
| Pobór mocy                | 250 / 390 / 400 W                  |
| Pobór prądu               | 1,1 / 1,71 / 1,68 A                |
| Prąd rozruchowy           | 3,15 / 3,0 A                       |
| Kondensator               | 5 µF / 450 V                       |
| Maks. wydajność           | 1450 m³/h                          |
| Maks. ciśnienie statyczne | 735 Pa                             |
| Temperatura otoczenia     | min. -25 °C; maks. 70 / 55 / 55 °C |

## Dane ErP (UE 327/2011)


|                            |          |
|----------------------------|----------|
| Sprawność całkowita        | 45 %     |
| Przepływ w pkt. optymalnym | 900 m³/h |
| Przyrost ciśnienia         | 439 Pa   |
| Regulacja prędkości (ErP)  | nie      |

## Budowa

|                        |                                      |
|------------------------|--------------------------------------|
| Wielkość               | 250 mm                               |
| Silnik                 | M2E074-EI                            |
| Materiał wirnika       | tworzywo PA                          |
| Liczba łopatek         | 7                                    |
| Kierunek obrotów       | w prawo, patrząc na wirnik           |
| Stopień ochrony        | IP44                                 |
| Klasa izolacji         | F                                    |
| Zabezpieczenie silnika | termik (TOP), podłączony wewnętrznie |
| Łożyskowanie           | kulkowe                              |
| Masa                   | 3,8 kg                               |

## Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



Measurement: LU-130850-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 15347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).  
Wartości przy maksymalnym obciążeniu; producent zastrzega możliwość zmian.

## Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199  
biuro@luftberg.pl · www.luftberg.pl

R2E250-RB06-19

# AC centrifugal fan - RadiCal

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KG  
Bachmühle 2 · D-74673 Mulfingen  
Phone +49 7938 81-0  
Fax +49 7938 81-110  
info1@de.ebmpapst.com  
www.ebmpapst.com

Nominal data

|                             |                   |      |      |         |
|-----------------------------|-------------------|------|------|---------|
| Type                        | R2E250-RB06-19    |      |      |         |
| Motor                       | M2E074-EI         |      |      |         |
| Phase                       |                   | 1~   | 1~   | 1~      |
| Nominal voltage             | VAC               | 230  | 230  | 230     |
| Frequency                   | Hz                | 50   | 60   | 60      |
| Method of obtaining data    |                   | ml   | ml   | ml      |
| Valid for approval/standard |                   | CE   | CE   | UL 2111 |
| Speed (rpm)                 | min <sup>-1</sup> | 2750 | 3100 | 3100    |
| Power consumption           | W                 | 250  | 390  | 400     |
| Current draw                | A                 | 1.1  | 1.71 | 1.68    |
| Capacitor                   | µF                | 5    | 5    | 5       |
| Capacitor voltage           | VDB               | 450  | 450  | 450     |
| Capacitor standard          |                   |      |      | UL      |
| Min. back pressure          | Pa                | 0    | 0    | 0       |
| Min. back pressure          | inH2O             | 0    | 0    | 0       |
| Min. ambient temperature    | °C                | -25  | -25  | -25     |
| Max. ambient temperature    | °C                | 70   | 55   | 55      |
| Starting current            | A                 | 3.15 | 3.0  |         |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

Data according to ErP Directive

|                                   |   | Actual | Req. 2015 |                               |                   |      |
|-----------------------------------|---|--------|-----------|-------------------------------|-------------------|------|
| 01 Overall efficiency $\eta_{es}$ | % | 45     | 45        | 09 Power consumption $P_e$    | kW                | 0.24 |
| 02 Measurement category           |   | A      |           | 09 Air flow $q_v$             | m³/h              | 900  |
| 03 Efficiency category            |   | Static |           | 09 Pressure increase $p_{fs}$ | Pa                | 439  |
| 04 Efficiency grade N             |   | 62     | 62        | 10 Speed (rpm) n              | min <sup>-1</sup> | 2775 |
| 05 Variable speed drive           |   | No     |           | 11 Specific ratio*            |                   | 1.00 |

Data obtained at optimum efficiency level.  
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

\* Specific ratio =  $1 + p_{fs} / 100\,000\text{ Pa}$  LU-130850



**R2E250-RB06-19**

# AC centrifugal fan - RadiCal

backward-curved, single-intake

## Technical description


|                                                                            |                                                              |
|----------------------------------------------------------------------------|--------------------------------------------------------------|
| Weight                                                                     | 3.8 kg                                                       |
| Fan size                                                                   | 250 mm                                                       |
| Rotor surface                                                              | Painted black                                                |
| Impeller material                                                          | PA plastic                                                   |
| Number of blades                                                           | 7                                                            |
| Direction of rotation                                                      | Clockwise, viewed toward rotor                               |
| Degree of protection                                                       | IP44; installation- and position-dependent as per EN 60034-5 |
| Insulation class                                                           | "F"                                                          |
| Moisture (F) / Environmental (H) protection class                          | F2-2                                                         |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                      |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                      |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request |
| Condensation drainage holes                                                | On rotor side                                                |
| Mode                                                                       | S1                                                           |
| Motor bearing                                                              | Ball bearing                                                 |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                                    |
| Motor protection                                                           | Thermal overload protector (TOP) internally connected        |
| With cable                                                                 | Variable                                                     |
| Protection class                                                           | I (with customer connection of protective earth)             |
| Conformity with standards                                                  | EN 60335-1; CE                                               |
| Approval                                                                   | CSA C22.2 No. 100; UL 1004-1                                 |

**R2E250-RB06-19**

# AC centrifugal fan - RadiCal


backward-curved, single-intake

## Product drawing



- |   |                                                                            |
|---|----------------------------------------------------------------------------|
| 1 | Accessory part: inlet ring 96359-2-4013, not included in scope of delivery |
| 2 | Max. clearance for screw 10 mm                                             |
| 3 | Cable PFA 4G AWG20, 4x crimped splices                                     |

## Connection diagram




|    |              |   |       |    |       |
|----|--------------|---|-------|----|-------|
| U1 | blue         | Z | brown | U2 | black |
| PE | green/yellow |   |       |    |       |

R2E250-RB06-19

AC centrifugal fan - RadiCal

backward-curved, single-intake

Curves: Air performance 50 Hz



Measurement: LU-130850-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | q <sub>v</sub> | P <sub>fs</sub> | q <sub>v</sub> | P <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|-------------------|-------------------|----------------|-----------------|----------------|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | dB(A)             | dB(A)             | m³/h           | Pa              | cfm            | inH <sub>2</sub> O |
| 1 | 230 | 50 | 2800              | 215            | 0.95 | 69                | 78                | 1495           | 0               | 880            | 0.00               |
| 2 | 230 | 50 | 2790              | 237            | 1.03 | 65                | 74                | 1290           | 200             | 760            | 0.80               |
| 3 | 230 | 50 | 2750              | 250            | 1.10 | 62                | 71                | 1000           | 400             | 590            | 1.61               |
| 4 | 230 | 50 | 2800              | 227            | 0.99 | 66                | 74                | 630            | 550             | 370            | 2.21               |


U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase



R2E250-RB06-19

AC centrifugal fan - RadiCal  
 backward-curved, single-intake

Curves: Air performance 60 Hz



Measurement: LU-130856-1  
  
 Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | q <sub>v</sub> | P <sub>fs</sub> | q <sub>v</sub> | P <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|-------------------|-------------------|----------------|-----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | dB(A)             | dB(A)             | m³/h           | Pa              | cfm            | inH2O           |
| 1 | 230 | 60 | 3200              | 345            | 1.51 | 73                | 81                | 1710           | 0               | 1005           | 0.00            |
| 2 | 230 | 60 | 3155              | 364            | 1.59 | 67                | 76                | 1425           | 300             | 840            | 1.20            |
| 3 | 230 | 60 | 3100              | 390            | 1.71 | 65                | 73                | 1115           | 500             | 655            | 2.01            |
| 4 | 230 | 60 | 3150              | 365            | 1.59 | 70                | 80                | 670            | 700             | 395            | 2.81            |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
 q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

