

KARTA KATALOGOWA

R2E280-RB01-01

Wentylator promieniowy AC RadiCal, łopatki zakrzywione do tyłu

Producent: ebm-papst




Zdjęcie poglądowe

Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 230 V	Wielkość	280 mm
Częstotliwość	50 Hz	Silnik	M2E074-GA
Prędkość obrotowa	2300 obr/min	Materiał wirnika	tworzywo PP
Pobór mocy	515 W	Liczba łopatek	6
Pobór prądu	2,25 A	Kierunek obrotów	w prawo, patrząc na wirnik
Prąd rozruchowy	3,12 A	Stopień ochrony	IP44
Kondensator	12 µF / 400 V	Klasa izolacji	F
Maks. wydajność	2800 m³/h	Zabezpieczenie silnika	termik (TOP), wyprowadzony, izolacja podstawowa
Maks. ciśnienie statyczne	600 Pa	Łożyskowanie	kulkowe
Temperatura otoczenia	-25...+40 °C	Masa	4,6 kg

Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



Measurement: LU-138289-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters must be checked in the installed unit.

Dane na okładce wg karty ebm-papst; strony producenta przetłumaczone z wersji rosyjskiej (oryg. RUS).
Wartości przy maksymalnym obciążeniu; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R2E280-RB01-01

AC centrifugal fan - RadiCal

backward curved

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	R2E280-RB01-01	
Motor	M2E074-GA	
Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Method of obtaining data		ml
Valid for approval/standard		-
Speed (rpm)	min ⁻¹	2300
Power consumption	W	515
Current draw	A	2.25
Capacitor	µF	12
Capacitor voltage	VDB	400
Min. back pressure	Pa	0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	40
Starting current	A	3.12

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change


ebmpapst

R2E280-RB01-01

AC centrifugal fan - RadiCal

backward curved

Technical description

Weight	4.6 kg
Fan size	280 mm
Motor size	74
Rotor surface	Painted black
Impeller material	PP plastic
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44
Degree of protection	Depending on installation position acc. to EN 60034-5
Insulation class	«F»
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0,75 mA
Motor protection	Thermal overload protector (TOP) brought out, with basic insulation
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1
Approval	EAC




R2E280-RB01-01

AC centrifugal fan - RadiCal

backward curved

Product drawing




- | | |
|---|--|
| 1 | Accessory part: inlet ring 28000-2-4013, not included in scope of delivery. |
| 2 | Max. clearance for screw 10 mm |
| 3 | Connection line silicone 6G 0.5 mm ² , 6 crimped wire end sleeves |

R2E280-RB01-01

AC centrifugal fan - RadiCal

backward curved

Connection diagram



U1	blue	Z	brown	U2	black
PE	green/yellow	TOP	2 x gray		




R2E280-RB01-01

AC centrifugal fan - RadiCal

backward curved

Curves: Air performance 50 Hz



Measurement: LU-138289-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters must be checked in the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	230	50	2525	440	1.91	2835	0	1670	0.00
2	230	50	2385	494	2.14	2250	250	1325	1.00
3	230	50	2300	515	2.25	1620	450	950	1.81
4	230	50	2415	480	2.08	1115	600	655	2.41

U = Power supply · f = Frequency · n = Speed (rpm) · P

e = Power consumption · I = Current draw · q_v = Air flow · p

fs = Pressure increase



ebm-papst