

KARTA KATALOGOWA

R3G190-RB01-08

Wentylator promieniowy EC, łopatki zakrzywione do tyłu


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 230 V (200...240 V)	Wielkość	190 mm
Częstotliwość	50/60 Hz	Silnik	M3G055-BD
Prędkość obrotowa	2370 obr/min	Materiał wirnika	tworzywo PA
Pobór mocy	38 W	Obudowa elektroniki	odlew aluminiowy
Pobór prądu	0,38 A	Liczba łopatek	7
Maks. wydajność	505 m³/h	Kierunek obrotów	w prawo, patrząc na wirnik
Maks. ciśnienie statyczne	240 Pa	Stopień ochrony	IP54
Temperatura otoczenia	-25...+60 °C	Klasa izolacji	B
		Zabezpieczenie silnika	ochrona przed zablokowaniem wirnika
		Łożyskowanie	kulkowe
		Podłączenie	listwa zaciskowa (STK)
		Masa	1 kg

Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



Measurement: LU-162050-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).
Wartości przy maksymalnym obciążeniu; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R3G190-RB01-08

EC centrifugal fan
backward-curved

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Nominal data

Type	R3G190-RB01-08	
Motor	M3G055-BD	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2370
Power consumption	W	38
Current draw	A	0.38
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



R3G190-RB01-08

EC centrifugal fan

backward-curved

Technical description

Weight	1 kg
Fan size	190 mm
Rotor surface	Thick-film passivated
Electronics housing material	Die-cast aluminum
Impeller material	PA plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Power limiter - Motor current limitation - Soft start - Thermal overload protection for electronics/motor - Line undervoltage detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	STK
Motor protection	Locked-rotor protection
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	C22.2 No.77 + CAN/CSA-E60730-1; UL 1004-7 + 60730; CCC




R3G190-RB01-08

EC centrifugal fan

backward-curved

Product drawing




1	Accessory part: Inlet ring 09576-2-4013, not included in scope of delivery
2	Max. clearance for screw 5 mm
3	Cable PVC AWG20, 1x 4-pole connector housing tyco 0-925075-0, 4x plug pin tyco 163555-6
3.1	N (blue)
3.2	L (black)
3.3	PE (green/yellow)
3.4	not used

R3G190-RB01-08

EC centrifugal fan

backward-curved

Accessory part




1 Accessory part: inlet ring 09576-2-4013 not included in scope of delivery

R3G190-RB01-08

EC centrifugal fan
backward-curved

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	CON 10	L	black	Power supply 230 VAC, 50 - 60 Hz, see nameplate for voltage range
	CON 11	N	blue	Neutral conductor
	CON 12	PE	green/yellow	Protective earth




R3G190-RB01-08

EC centrifugal fan

backward-curved

Curves: Air performance 50 Hz



Measurement: LU-162050-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH2O
1	230	50	2450	31	0.32	505	0	300	0.00
2	230	50	2400	33	0.34	415	100	245	0.40
3	230	50	2370	38	0.38	300	180	175	0.72
4	230	50	2405	33	0.34	170	240	100	0.96

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

