

KARTA KATALOGOWA

R3G250-RR09-P1

Wentylator promieniowy EC RadiCal, łopatki zakrzywione do tyłu, jednostronnie ssący

Producent: ebm-papst



Dane znamionowe

Napięcie znamionowe	110 V DC (77...138 V)
Prędkość obrotowa	3800 obr/min
Pobór mocy	540 W
Pobór prądu	4,9 A
Maks. wydajność	2135 m³/h
Maks. ciśnienie statyczne	1069 Pa
Temperatura otoczenia	-40...+60 °C

Budowa


Średnica wirnika	250 mm
Materiał wirnika	tworzywo PA
Liczba łopatek	7
Stopień ochrony	IP55
Klasa izolacji	F
Zabezpieczenie silnika	termik (TOP)
Masa	4,1 kg

Dane ErP (UE 327/2011)

Sprawność całkowita	56,8 %
Przepływ w pkt. optymalnym	1210 m³/h
Przyrost ciśnienia	813 Pa
Regulacja obrotów	tak (0-10 V / PWM / MODBUS)

Charakterystyka przepływowa

Curves: Air performance



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-172892-1
Measurement: LU-172878-1
Measurement: LU-172890-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).

Wartości znamionowe dla punktu maksymalnego obciążenia; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R3G250-RR09-P1

EC centrifugal fan - RadiCal

backward-curved, single-intake

for rail applications


ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	R3G250-RR09-P1	
Motor	M3G084-DF	

Nominal voltage	VDC	110
Nominal voltage range	VDC	77 .. 138
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	3800
Power consumption	W	540
Current draw	A	4.9
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	56.8	48.6	09 Power consumption P_e	kW	0.53
02 Measurement category		A		09 Air flow q_v	m ³ /h	1210
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	813
04 Efficiency grade N		70.2	62	10 Speed (rpm) n	min ⁻¹	3805
05 Variable speed drive		Yes		11 Specific ratio*		1.01

Data obtained at optimum efficiency level.

 * Specific ratio = $1 + p_b / 100\,000\text{ Pa}$

LU-172878

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).



R3G250-RR09-P1

EC centrifugal fan - RadiCal

backward-curved, single-intake

for rail applications

Technical description

Weight	4.1 kg
Size	250 mm
Motor size	84
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PA plastic UL94 V0
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H3
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing; (sealed)
Technical features	- Output 10 VDC, max. 10 mA - Operation and alarm display - Alarm relay - Run monitoring - Power limiter - Motor current limitation - RS-485 MODBUS-RTU - Soft start - EEPROM write cycles: 100,000 maximum - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection - Reverse polarity protection
EMC regulations	According to EN 50121-3-2
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Lateral
Protection class assignment	I; If a protective earth is connected by the customer This component for installation may have several local protection classes. This information relates to this component's basic design. The final protection class is based on the component's intended installation and connection.
Conformity with standards	EN 15085-1, CPC3; EN 45545-2, HL3; EN 50155; EN 61373, Cat. 1B; CE
Approval	EAC



R3G250-RR09-P1

EC centrifugal fan - RadiCal

backward-curved, single-intake

for rail applications

Comment

If supply potential (e.g. 230 VAC) is passed through the alarm relay, the SELV signal wires lose their property of reinforced insulation, meaning they then have only basic insulation

The SELV property (reinforced insulation) is not lost when voltages of up to 110 VDC are passed through the alarm relay. EMC regulation: EN 50121-3-2 in preparation; speed limit 4000 rpm




R3G250-RR09-P1

EC centrifugal fan - RadiCal

backward-curved, single-intake

for rail applications

Product drawing



- | | |
|---|---|
| 1 | Accessory part: Inlet ring 96420-2-4013 (not included in scope of delivery) |
| 2 | Max. clearance for screw 16 mm |
| 3 | Cable, halogen-free, railway application EN 45545, 4G 1.5 mm ²
3x wire-end ferrule, 1x wire not routed externally |
| 4 | Cable, halogen-free, railway application EN 45545, 7x 0.5 mm ²
7x wire-end ferrule |




R3G250-RR09-P1

EC centrifugal fan - RadiCal

backward-curved, single-intake

for rail applications

Accessory part



Inlet ring 96420-2-4013


R3G250-RR09-P1

EC centrifugal fan - RadiCal

backward-curved, single-intake

for rail applications

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
1	1	PE	green/yellow	Protective earth
1	2	PE	-	not brought out via wire
1	3	-	black	Power supply, GND, voltage range see nameplate
1	5	+	brown	Power supply, see nameplate for voltage range
2	6	COM	gray	Status relay, floating status contact, common connection, contact rating 250 VAC/30 VDC max. 2 A (AC1), min. 1 mA/5 VDC, reinforced insulation on control interface side, basic insulation on supply side in accordance with EN 50124-1
2	7	NO	orange	Status relay, floating status contact, normally open contact, contact rating 250 VAC/30 VDC max. 2 A (AC1), min. 1 mA/5 VDC, reinforced insulation on control interface side, basic insulation on supply side in accordance with EN 50124-1
2	8	0-10 V	yellow	Analog input (set value) SELV, 0-10 V, $R_i = 100\text{ k}\Omega$, adjustable curve
2	10	RSB	brown	RS-485 interface for MODBUS, RSB; SELV, bus termination resistor provided by customer
2	11	RSA	white	RS-485 interface for MODBUS, RSA; SELV, bus termination resistor provided by customer
2	12	GND	blue	Reference ground for control interface; SELV
2	13	+10 V	red	Fixed voltage output 10 VDC, SELV, +10 V $\pm 3\%$, max. 10 mA, short-circuit-proof, power supply for external devices (e.g. potentiometers)




R3G250-RR09-P1

EC centrifugal fan - RadiCal

backward-curved, single-intake

for rail applications

Curves: Air performance



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-172892-1
Measurement: LU-172878-1
Measurement: LU-172890-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _V	P _{fs}	q _V	P _{fs}
	V	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	138	4000	492	3.56			2135	0	1255	0.00
2	138	3945	557	4.04			1790	426	1055	1.71
3	138	3835	555	4.02			1240	813	730	3.26
4	138	3955	553	4.00			835	1069	495	4.29
5	110	3860	447	4.06	78	86	2055	0	1210	0.00
6	110	3815	510	4.64	75	83	1735	400	1020	1.61
7	110	3800	540	4.90	72	80	1230	800	725	3.21
8	110	3840	510	4.63	74	82	815	1000	480	4.01
9	77	2755	173	2.25			1445	0	850	0.00
10	77	2735	197	2.56			1230	200	725	0.80
11	77	2725	211	2.73			880	412	520	1.65
12	77	2735	197	2.56			580	516	345	2.07

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side · q_V = Air flow
P_{fs} = Pressure increase

