

KARTA KATALOGOWA

R3G400-RS03-H3

Wentylator promieniowy EC RadiCal, łopatki zakrzywione do tyłu, jednostronnie ssący

Producent: ebm-papst



Zdjęcie poglądowe


Dane znamionowe	
Napięcie znamionowe	1~ 230 V (200...277 V)
Częstotliwość	50/60 Hz
Prędkość obrotowa	1500 obr/min
Pobór mocy	500 W
Pobór prądu	2,2 A
Maks. wydajność	5065 m³/h
Maks. ciśnienie statyczne	450 Pa
Temperatura otoczenia	-25...+50 °C

Dane ErP (UE 327/2011)	
Sprawność całkowita	66,4 %
Przepływ w pkt. optymalnym	3200 m³/h
Przyrost ciśnienia	345 Pa
Regulacja obrotów	tak (0-10 V / PWM / MODBUS)

Budowa	
Średnica wirnika	400 mm
Materiał wirnika	tworzywo PP
Liczba łopatek	6
Stopień ochrony	IP55
Klasa izolacji	F
Zabezpieczenie silnika	termik (TOP)
Masa	6,4 kg

Charakterystyka przepływowa

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-183601-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).

Wartości znamionowe dla punktu maksymalnego obciążenia; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R3G400-RS03-H3

EC centrifugal fan - RadiCal

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	R3G400-RS03-H3	
Motor	M3G084-FA	

Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60

Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1500
Power consumption	W	500
Current draw	A	2.2
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	66.4	48.4	09 Power consumption P_{ed}	kW	0.51
02 Measurement category		A		09 Air flow q_v	m ³ /h	3200
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	345
04 Efficiency grade N		80	62	10 Speed (rpm) n	min ⁻¹	1480
05 Variable speed drive		Yes		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.

The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-183601



R3G400-RS03-H3

EC centrifugal fan - RadiCal

backward-curved, single-intake

Technical description

Weight	6.4 kg
Size	400 mm
Motor size	84
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic (black)
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Operation and alarm display - Alarm relay - Integrated PID controller - Power limiter - Motor current limitation - PFC, active - RS-485 MODBUS-RTU - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	≤ 3.5 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 61800-5-1; EN 60335-1; CE
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC; UL 1004-7 + 60730-1




R3G400-RS03-H3

EC centrifugal fan - RadiCal

backward-curved, single-intake

Product drawing





- | | |
|---|--|
| 1 | Accessory part: Inlet ring 54476-2-4013 not included in scope of delivery. |
| 2 | Max. clearance for screw 16 mm |
| 3 | Cable PVC AWG18, 5x crimped ferrules |
| 4 | Cable PVC AWG22, 5x crimped ferrules |

R3G400-RS03-H3

EC centrifugal fan - RadiCal

backward-curved, single-intake

Accessory part




Inlet ring 54476-2-4013

R3G400-RS03-H3

EC centrifugal fan - RadiCal

backward-curved, single-intake

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
1	1, 2	PE	green/yellow	Protective earth
1	3	N	blue	Power supply, neutral conductor, 50/60 Hz
1	5	L	black	Power supply, phase, 50/60 Hz
1	6	NC	white 1	Status relay, floating status contact; break for failure, contact rating 250 VAC / 2A (AC1) / min. 10 mA, basic insulation on supply side and reinforced insulation on control interface side
1	7	COM	white 2	Status relay, floating status contact; common connection, contact rating 250 VAC / 2A (AC1) / min. 10 mA, basic insulation on supply side and reinforced insulation on control interface side
2	8	0-10V	yellow	Analog input (set value); 0-10 V; R _i = 100 kΩ; adjustable curve
2	10	RSB	brown	RS485 interface for MODBUS, RSB
2	11	RSA	white	RS485 interface for MODBUS, RSA
2	12	GND	blue	Reference ground for control interface, SELV
2	13	+10V	red	Fixed voltage output 10 VDC, +10 V ±3%; max. 10 mA; short-circuit-proof; power supply for external devices (e.g. pot)




R3G400-RS03-H3

EC centrifugal fan - RadiCal

backward-curved, single-intake

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2\%$

Measurement: LU-183601-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	230	50	1535	395	1.73	5065	0	2980	0.00
2	230	50	1525	500	2.20	4300	200	2530	0.80
3	230	50	1500	500	2.20	3140	350	1850	1.41
4	230	50	1515	500	2.20	2250	450	1325	1.81
5	230	50	1400	297	1.30	4610	0	2715	0.00
6	230	50	1400	406	1.78	3955	170	2325	0.68
7	230	50	1400	433	1.90	2970	314	1750	1.26
8	230	50	1400	411	1.80	2075	383	1220	1.54
9	230	50	1200	187	0.82	3950	0	2325	0.00
10	230	50	1200	256	1.12	3390	125	1995	0.50
11	230	50	1200	273	1.20	2545	231	1500	0.93
12	230	50	1200	259	1.13	1780	281	1045	1.13
13	230	50	1000	108	0.48	3295	0	1940	0.00
14	230	50	1000	148	0.65	2825	87	1660	0.35
15	230	50	1000	158	0.69	2120	160	1250	0.64
16	230	50	1000	150	0.65	1480	195	870	0.78

U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

