

KARTA KATALOGOWA

R3G500-RS06-G1

Wentylator promieniowy EC RadiCal, łopatki zakrzywione do tyłu, jednostronnie ssący


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 230 V (200...277 V)	Średnica wirnika	500 mm
Częstotliwość	50/60 Hz	Materiał wirnika	tworzywo PP
Prędkość obrotowa	750 obr/min	Liczba łopatek	7
Pobór mocy	250 W	Stopień ochrony	IP55
Pobór prądu	1,1 A	Klasa izolacji	F
Maks. wydajność	5715 m³/h	Masa	8,92 kg
Maks. ciśnienie statyczne	300 Pa		
Temperatura otoczenia	-25...+60 °C		
Dane ErP (UE 327/2011)			
Sprawność całkowita	58,5 %		
Przepływ w pkt. optymalnym	3410 m³/h		
Przyrost ciśnienia	136 Pa		
Regulacja obrotów	tak (0-10 V / PWM / MODBUS)		

Charakterystyka przepływowa

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

-152274-1

Date: 2026-06-08

943

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).

Wartości znamionowe dla punktu maksymalnego obciążenia; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199

biuro@luftberg.pl · www.luftberg.pl

R3G500-RS06-G1

EC centrifugal fan - RadiCal

backward-curved, single-intake



Nominal data

Type	R3G500-RS06-G1	
Motor	M3G084-FA	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	750
Power consumption	W	250
Current draw	A	1.1
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60
Starting current	A	1.8

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual		Req. 2015	
01 Overall efficiency η_{es}	%	58.5		45.2	
02 Measurement category		A			
03 Efficiency category		Static			
04 Efficiency grade N		75.3		62	
05 Variable speed drive		Yes			
09 Power consumption P_{ed}	kW			0.24	
09 Air flow q_v	m³/h			3410	
09 Pressure increase p_{fs}	Pa			136	
10 Speed (rpm) n	min ⁻¹			740	
11 Specific ratio*				1.00	

Data obtained at optimum efficiency level.
The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$
LU-152274

R3G500-RS06-G1

EC centrifugal fan - RadiCal

backward-curved, single-intake

Technical description


Weight	8.92 kg
Size	500 mm
Motor size	84
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Operation and alarm display - Alarm relay - Integrated PID controller - Power limiter - Motor current limitation - PFC, active - RS-485 MODBUS-RTU - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from supply - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	≤ 3.5 mA
Motor protection	Thermal switch auto reset, internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 61800-5-1; EN 60335-1; CE
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC; UL 1004-7 + 60730-1

R3G500-RS06-G1

EC centrifugal fan - RadiCal

backward-curved, single-intake

Product drawing





- | | |
|---|---|
| 1 | Accessory part: inlet ring 50901-2-2943 not included in scope of delivery |
| 2 | Max. clearance for screw 16 mm |
| 3 | Cable PVC AWG18, 5x crimped ferrules |
| 4 | Cable PVC AWG22, 5x crimped ferrules |

R3G500-RS06-G1

EC centrifugal fan - RadiCal

backward-curved, single-intake

Accessory part




1 Accessory part: inlet ring 50901-2-2943

R3G500-RS06-G1

EC centrifugal fan - RadiCal

backward-curved, single-intake

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
1	1, 2	PE	green/yellow	Protective earth
1	3	N	blue	Power supply, neutral conductor, 50/60 Hz
1	5	L	black	Power supply, phase, 50/60 Hz
1	6	NC	white 1	Status relay, floating status contact; break for failure, contact rating 250 VAC / 2A (AC1) / min. 10 mA, basic insulation on supply side and reinforced insulation on control interface side
1	7	COM	white 2	Status relay, floating status contact; common connection, contact rating 250 VAC / 2A (AC1) / min. 10 mA, basic insulation on supply side and reinforced insulation on control interface side
2	8	0-10V	yellow	Analog input (set value); 0-10 V; R _i = 100 kΩ; adjustable curve
2	10	RSB	brown	RS485 interface for MODBUS, RSB
2	11	RSA	white	RS485 interface for MODBUS, RSA
2	12	GND	blue	Reference ground for control interface, SELV
2	13	+10V	red	Fixed voltage output 10 VDC, +10 V ±3%; max. 10 mA; short-circuit-proof; power supply for external devices (e.g. pot)

R3G500-RS06-G1

EC centrifugal fan - RadiCal

backward-curved, single-intake

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

-152274-1
Date: 2026-06-08
943

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	in. wg
1	1~	230	50	825	226	1.00	5715	0	3365	0.00
2	1~	230	50	770	250	1.10	4495	80	2645	0.32
3	1~	230	50	750	250	1.10	3085	150	1815	0.60
4	1~	230	50	805	250	1.10	1640	220	965	0.88
5	1~	230	50	650	111	0.49	4500	0	2650	0.00
6	1~	230	50	650	152	0.67	3800	57	2235	0.23
7	1~	230	50	650	168	0.74	2705	116	1590	0.47
8	1~	230	50	650	133	0.58	1325	145	780	0.58
9	1~	230	50	550	67	0.30	3810	0	2240	0.00
10	1~	230	50	550	92	0.41	3215	41	1890	0.16
11	1~	230	50	550	102	0.45	2290	83	1345	0.33
12	1~	230	50	550	80	0.35	1120	104	660	0.42
13	1~	230	50	450	37	0.16	3115	0	1835	0.00
14	1~	230	50	450	50	0.22	2630	28	1545	0.11
15	1~	230	50	450	56	0.25	1870	56	1100	0.22
16	1~	230	50	450	44	0.19	920	69	540	0.28

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase