

KARTA KATALOGOWA

R3G630-RK57-31

Wentylator promieniowy EC RadiCal, łopatki zakrzywione do tyłu, jednostronnie ssący

Producent: ebm-papst



Zdjęcie poglądowe


Dane znamionowe	
Napięcie znamionowe	1~ 230 V (200...277 V)
Częstotliwość	50/60 Hz
Prędkość obrotowa	730 obr/min
Pobór mocy	500 W
Pobór prądu	2,2 A
Maks. wydajność	10495 m³/h
Maks. ciśnienie statyczne	320 Pa
Temperatura otoczenia	-25...+40 °C

Dane ErP (UE 327/2011)	
Sprawność całkowita	63,5 %
Przepływ w pkt. optymalnym	6530 m³/h
Przyrost ciśnienia	159 Pa
Regulacja obrotów	tak (0-10 V / PWM / MODBUS)

Budowa	
Średnica wirnika	630 mm
Materiał wirnika	tworzywo PP
Liczba łopatek	6
Stopień ochrony	IP55
Klasa izolacji	F
Zabezpieczenie silnika	termik (TOP)
Masa	25 kg

Charakterystyka przepływowa

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-152717-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).

Wartości znamionowe dla punktu maksymalnego obciążenia; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R3G630-RK57-31

EC centrifugal fan - RadiCal

backward-curved



Nominal data

Type	R3G630-RK57-31	
Motor	M3G112-GA	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	730
Power consumption	W	500
Current draw	A	2.2
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	40
Starting current	A	4.2

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	63.5	48.5	09 Power consumption P_{ed}	kW	0.5
02 Measurement category		A		09 Air flow q_v	m³/h	6530
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	159
04 Efficiency grade N		77.2	62	10 Speed (rpm) n	min ⁻¹	740
05 Variable speed drive		Yes		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$ LU-152717



R3G630-RK57-31

EC centrifugal fan - RadiCal

backward-curved

Technical description

Weight	25 kg
Fan size	630 mm
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F4-1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Operation and alarm display - Alarm relay - Integrated PID controller - Power limiter - Motor current limitation - PFC, active - RS-485 MODBUS-RTU - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from supply - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 61800-5-1; EN 60335-1; CE
Approval	CCC; EAC; C22.2 No.77 + CAN/CSA-E60730-1; UL 1004-7 + 60730




R3G630-RK57-31

EC centrifugal fan - RadiCal

backward-curved

Product drawing




1	Accessory part: inlet ring 63300-2-4013 not included in scope of delivery
2	Max. clearance for screw 16 mm
3	Cable PVC AWG18, 5x crimped ferrules
4	Cable PVC AWG22, 5x crimped ferrules

R3G630-RK57-31

EC centrifugal fan - RadiCal

backward-curved

Accessory part




Accessory part: inlet ring 63300-2-4013 not included in scope of delivery

R3G630-RK57-31

EC centrifugal fan - RadiCal

backward-curved

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
1	1, 2	PE	green/yellow	Protective earth
1	3	N	blue	Power supply, neutral conductor, 50/60 Hz
1	5	L	black	Power supply, phase, 50/60 Hz
1	6	NC	white 1	Status relay, floating status contact; break for failure, contact rating 250 VAC / 2A (AC1) / min. 10 mA, basic insulation on supply side and reinforced insulation on control interface side
1	7	COM	white 2	Status relay, floating status contact; common connection, contact rating 250 VAC / 2A (AC1) / min. 10 mA, basic insulation on supply side and reinforced insulation on control interface side
2	8	0-10V	yellow	Analog input (set value); 0-10 V; R _i = 100 kΩ; adjustable curve
2	10	RSB	brown	RS485 interface for MODBUS, RSB
2	11	RSA	white	RS485 interface for MODBUS, RSA
2	12	GND	blue	Reference ground for control interface, SELV
2	13	+10V	red	Fixed voltage output 10 VDC, +10 V ±3%; max. 10 mA; short-circuit-proof; power supply for external devices (e.g. pot)

R3G630-RK57-31

EC centrifugal fan - RadiCal

backward-curved

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-152717-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	qv	P _{fs}	qv	P _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa	CFM	inH2O
1	230	50	820	468	2.04	69	76	80	10495	0	6175	0.00
2	230	50	760	500	2.20	61	69	73	8155	100	4800	0.40
3	230	50	730	500	2.20	57	65	69	5705	180	3355	0.72
4	230	50	765	500	2.20	61	69	72	3355	240	1975	0.96
5	230	50	650	231	1.01	63	70	75	8300	0	4885	0.00
6	230	50	650	310	1.35	57	65	69	6960	72	4095	0.29
7	230	50	650	347	1.51	54	62	66	5045	141	2970	0.57
8	230	50	650	307	1.34	57	64	68	2845	174	1675	0.70
9	230	50	550	140	0.61	59	66	70	7020	0	4135	0.00
10	230	50	550	188	0.82	53	60	65	5890	52	3465	0.21
11	230	50	550	210	0.91	50	58	62	4265	101	2510	0.41
12	230	50	550	186	0.81	53	60	64	2410	125	1420	0.50
13	230	50	450	77	0.33	54	61	65	5745	0	3380	0.00
14	230	50	450	103	0.45	48	55	60	4820	35	2835	0.14
15	230	50	450	115	0.50	45	53	57	3490	68	2055	0.27
16	230	50	450	102	0.44	48	55	59	1970	83	1160	0.33

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · qv = Air flow · p_{fs} = Pressure increase

