

KARTA KATALOGOWA

R4D355-AE03-10

Wentylator promieniowy AC, łopatki zakrzywione do tyłu, jednostronnie ssący

Producent: ebm-papst




Zdjęcie poglądowe

Dane znamionowe

Napięcie znamionowe	3~ 400 V Δ / 400 V Y
Częstotliwość	50 Hz
Prędkość obrotowa	1400 / 1200 obr/min
Pobór mocy	190 / 130 W
Pobór prądu	0,51 / 0,22 A
Maks. wydajność	2810 m³/h
Maks. ciśnienie statyczne	270 Pa
Temperatura otoczenia	-25...+40 °C

Budowa

Średnica wirnika	355 mm
Materiał wirnika	tworzywo PP
Liczba łopatek	6
Stopień ochrony	IP44
Klasa izolacji	B
Zabezpieczenie silnika	termik (TOP)
Masa	4,9 kg

Charakterystyka przepływowa
Curves: Air performance 50 Hz Δ

 Measurement: LU-31018-1
 Measurement: LU-30959-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).

Dwie wartości odpowiadają połączeniu Δ / Y (kolumny karty producenta); producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

 tel. +48 600 100 371 · tel. +48 604 959 199
 biuro@luftberg.pl · www.luftberg.pl

R4D355-AE03-10

AC centrifugal fan

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	R4D355-AE03-10		
Motor	M4D074-EI		
Phase		3~	3~
Nominal voltage	VAC	400	400
Wiring		Δ	Y
Frequency	Hz	50	50
Method of obtaining data		fa	fa
Valid for approval/standard		-	-
Speed (rpm)	min ⁻¹	1400	1200
Power consumption	W	190	130
Current draw	A	0.51	0.22
Min. back pressure	Pa	0	0
Min. back pressure	in. wg	0	0
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	40	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
 Subject to change



R4D355-AE03-10

AC centrifugal fan

backward-curved, single-intake

Technical description

Weight	4.9 kg
Size	355 mm
Motor size	74
Rotor surface	Painted black
Impeller material	PP plastic
Number of blades	6
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1
Approval	EAC




R4D355-AE03-10

AC centrifugal fan

backward-curved, single-intake

Product drawing




- | | |
|---|---|
| 1 | Accessory part: Inlet ring 57357-2-4013 not included in scope of delivery |
| 2 | Max. clearance for screw 10 mm |
| 3 | Cable AWG20 9G 0.5 mm ² , 4x crimped splices |

R4D355-AE03-10

AC centrifugal fan
backward-curved, single-intake

Connection diagram



Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2x gray
PE	green/yellow				




R4D355-AE03-10

AC centrifugal fan

backward-curved, single-intake

Curves: Air performance 50 Hz Δ



Measurement: LU-31018-1
Measurement: LU-30959-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	Δ	400	50	1400	190	0.51	2810	0	1655	0.00
2	Δ	400	50	1360	227	0.54	2275	120	1340	0.48
3	Δ	400	50	1340	250	0.56	1715	220	1010	0.88
4	Δ	400	50	1350	242	0.55	1265	270	745	1.08
5	Y	400	50	1200	130	0.22	2425	0	1430	0.00
6	Y	400	50	1130	150	0.26	1860	80	1095	0.32
7	Y	400	50	1085	160	0.28	1380	142	810	0.57
8	Y	400	50	1100	157	0.28	1030	181	605	0.73

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

