

KARTA KATALOGOWA

R4D500-AQ05-01

Wentylator promieniowy AC, łopatki zakrzywione do tyłu, jednostronnie ssący

Producent: ebm-papst



Zdjęcie poglądowe

Dane znamionowe


Napięcie znamionowe	3~ 230/277 V Δ · 400/480 V Y (50/60 Hz)
Częstotliwość	50/60 Hz
Prędkość obrotowa	1410 / 1670 obr/min
Pobór mocy	1450 / 2400 W
Pobór prądu	5,54 / 6,75 A (Δ) · 3,2 / 3,9 A (Y)
Maks. wydajność	8205 m³/h
Maks. ciśnienie statyczne	603 Pa
Temperatura otoczenia	-40...+95 °C (60 Hz: +70 °C)

Budowa

Średnica wirnika	500 mm
Materiał wirnika	blacha aluminiowa
Liczba łopatek	9
Stopień ochrony	IP54
Klasa izolacji	F
Zabezpieczenie silnika	termik (TOP)
Masa	25,5 kg

Charakterystyka przepływowa

Curves: Air performance 50 Hz



Measurement: LU-101370-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).
Wartości dla 50 Hz / 60 Hz; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R4D500-AQ05-01

AC centrifugal fan
backward-curved

Nominal data

Type	R4D500-AQ05-01				
Motor	M4D138-LA				
Phase		3~	3~	3~	3~
Nominal voltage	VAC	230	277	400	480
Wiring		Δ	Δ	Y	Y
Frequency	Hz	50	60	50	60
Method of obtaining data		ml	fa	ml	ml
Valid for approval/standard		CE	CE	CE	CE
Speed (rpm)	min ⁻¹	1410	1670	1410	1670
Power consumption	W	1450	2400	1450	2400
Current draw	A	5.54	6.75	3.2	3.9
Min. back pressure	Pa	0	0	0	0
Min. back pressure	in. wg	0	0	0	0
Min. ambient temperature	°C	-40	-40	-40	-40
Max. ambient temperature	°C	95	70	95	70

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



R4D500-AQ05-01

AC centrifugal fan

backward-curved

Technical description


Weight	25.5 kg
Fan size	500 mm
Rotor surface	Cast in aluminum
Impeller material	Sheet aluminum
Number of blades	9
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	F3-1
Ambient temperature note	Occasional start-up between -40°C and -25°C is permissible. For continuous operation at temperatures below -25°C (e.g. refrigeration applications) we recommend our fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	On rotor and stator sides
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) with basic insulation
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60034-1 (2010); EN 61800-5-1
Approval	CSA C22.2 No. 100; UL 1004-1; EAC

R4D500-AQ05-01

AC centrifugal fan

backward-curved

Product drawing




- | | |
|---|--|
| 1 | Cable silicone 9x 0.75 mm ² , 9x crimped splices |
| 2 | Accessory part: inlet ring 63072-2-4013 not included in scope of delivery. Other inlet rings on request. |
| 3 | Max. clearance for screw 18 mm |

R4D500-AQ05-01

AC centrifugal fan
backward-curved

Connection diagram



Change of rotation direction by reversing two phases

Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2x gray
PE	green/yellow				




R4D500-AQ05-01

AC centrifugal fan

backward-curved

Curves: Air performance 50 Hz



Measurement: LU-101370-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	q _v	p _{ts}	q _v	p _{ts}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	Y	400	50	1430	1210	2.87	78	86	8205	0	4830	0.00
2	Y	400	50	1415	1383	3.07	74	82	6625	250	3900	1.00
3	Y	400	50	1410	1450	3.20	70	78	4780	501	2815	2.01
4	Y	400	50	1425	1248	2.90	71	78	3250	603	1915	2.42

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{ts} = Pressure increase




R4D500-AQ05-01

AC centrifugal fan

backward-curved

Curves: Air performance 60 Hz



Measurement: LU-101368-1
Measurement: LU-101369-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	Y	480	60	1695	2008	3.41	84	91	9755	0	5740	0.00
2	Y	480	60	1675	2291	3.69	79	86	7770	350	4575	1.41
3	Y	480	60	1670	2400	3.90	75	82	5545	700	3265	2.81
4	Y	480	60	1690	2021	3.38	76	83	3620	850	2130	3.41
5	Y	400	60	1645	1883	3.36	82	90	9440	0	5555	0.00
6	Y	400	60	1615	2144	3.76	78	85	7530	327	4430	1.31
7	Y	400	60	1600	2240	3.90	74	81	5370	656	3160	2.63
8	Y	400	60	1640	1894	3.39	75	82	3510	800	2065	3.21

Wired = Wiring · U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · P_{fs} = Pressure increase

