

KARTA KATALOGOWA

R4E160-AB01-01

Wentylator promieniowy AC, łopatki zakrzywione do przodu, jednostronnie ssący

Producent: ebm-papst




Zdjęcie poglądowe

Dane znamionowe		Budowa	
Napięcie znamionowe	1~ 230 V	Średnica wirnika	160 mm
Częstotliwość	50/60 Hz	Materiał wirnika	stal ocynkowana
Prędkość obrotowa	1300 / 1400 obr/min	Stopień ochrony	IP44
Pobór mocy	67 / 90 W	Klasa izolacji	B
Pobór prądu	0,3 / 0,4 A	Zabezpieczenie silnika	termik (TOP)
Kondensator	2 µF / 450 V	Masa	1,7 kg
Wydajność (swobodny wypływ)	410 / 445 m³/h		
Maks. ciśnienie statyczne	148 Pa		
Maks. temp. otoczenia	+65 °C (50 Hz) / +60 °C (60 Hz)		

Charakterystyka przepływowa

Charts: Air flow 50 Hz



Dane na podstawie karty producenta ebm-papst (oryginał na kolejnych stronach).
Wartości dla 50 Hz / 60 Hz; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199
biuro@luftberg.pl · www.luftberg.pl

R4E160-AB01-01

AC centrifugal fan

forward curved, single inlet

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2

74673 Mulfingen

Phone: +49 7938 81-0

Fax: +49 7938 81-110

www.ebmpapst.com

info1@de.ebmpapst.com

Nominal data

Type	R4E160-AB01-01		
Motor	M4E068-CF		
Phase		1~	1~
Nominal voltage	[V]	230	230
Frequency	[Hz]	50	60
Type of data definition		rfa	rfa
Valid for approval / standard		CE	CE
Speed	[min ⁻¹]	1300	1400
Power input	[W]	67	90
Current draw	[A]	0.3	0.4
Motor capacitor	[µF]	2	2
Capacitor voltage	[VDB]	450	450
Capacitor standard		P0 (CE)	P0 (CE)
Min. back pressure	[Pa]	0	0
Max. ambient temperature	[°C]	65	60
Air flow	[m ³ /h]	410	445
Back pressure	[Pa]	0	0
Sound pressure level	[dB(A)]	65	67

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

R4E160-AB01-01

AC centrifugal fan

forward curved, single inlet

Technical features


Leakage current	< 0,75 mA
Size	160 mm
Operation mode	S1
Direction of rotation	Clockwise, seen on rotor
Mounting position	Any
Insulation class	"B"
Cable exit	Variable
Condensate discharge holes	None
Bearing-motor	Ball bearing
Mass	1.7 kg
Material of impeller	Sheet steel, galvanised
Motor protection	Thermal overload protector (TOP) wired internally
Product conforming to standard	CE; EN 60335-1
Surface of rotor	Partially cast in aluminium
Type of protection	IP 44 - depending on position
Protection class	I
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Approval	CCC

R4E160-AB01-01

AC centrifugal fan


forward curved, single inlet

Product drawing



- | | |
|---|---|
| 1 | Connection line PVC, 4x brass lead tips crimped |
| 2 | Screw depth max. 5 mm |
| 3 | Direction of rotation clockwise, seen on rotor |

Connection screen




U1	blue	Z	brown	U2	black
PE	green/yellow				

R4E160-AB01-01

AC centrifugal fan

forward curved, single inlet

Charts: Air flow 50 Hz



Measured values


	U	f	n	P ₁	I	$\dot{V}$	P _{fa}
	[V]	[Hz]	[min ⁻¹]	[W]	[A]	[m ³ /h]	[Pa]
1	230	50	1300	66	0.30	410	0
2	230	50	1345	60	0.26	340	70
3	230	50	1385	56	0.24	255	131
4	230	50	1420	51	0.23	170	148

R4E160-AB01-01

AC centrifugal fan

forward curved, single inlet

Charts: Air flow 60 Hz



Measured values

	U	f	n	P ₁	I	$\dot{V}$	P _{fa}
	[V]	[Hz]	[min ⁻¹]	[W]	[A]	[m ³ /h]	[Pa]
1	230	60	1400	90	0.40	445	0
2	230	60	1510	82	0.36	375	90
3	230	60	1595	76	0.34	290	182
4	230	60	1660	70	0.31	180	204