


KARTA KATALOGOWA

W2S130-AA19-38

Wentylator osiowy kompaktowy AC


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	2~ 400 V	Wielkość	130 mm
Częstotliwość	50 / 60 Hz	Silnik	M2S052-CA
Prędkość obrotowa	2800 / 3200 obr/min	Materiał wirnika	blacha stalowa malowana na czarno
Pobór mocy	41 / 38 W	Obudowa	odlew aluminiowy malowany na czarno
Pobór prądu	0,16 / 0,13 A	Liczba łopatek	7
Prąd rozruchowy	0,25 / 0,21 A	Kierunek obrotów	w lewo, patrząc na wirnik
Maks. przeciwnieście	80 / 120 Pa	Stopień ochrony	IP20
Temperatura otoczenia	min. -25 °C; maks. 50 / 70 °C	Klasa izolacji	B
		Zabezpieczenie silnika	termik (TOP), podłączony wewnętrznie
		Łożyskowanie	kulkowe
		Masa	1,1 kg

Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



Measurement: LU-69605-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).

Wartości przy swobodnym wydmuchu; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199

biuro@luftberg.pl · www.luftberg.pl

W2S130-AA19-38

AC axial compact fan

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Nominal data

Type	W2S130-AA19-38		
Motor	M2S052-CA		
Phase		2~	2~
Nominal voltage	VAC	400	400
Frequency	Hz	50	60
Method of obtaining data		fa	fa
Valid for approval/standard		CE	CE
Speed (rpm)	min ⁻¹	2800	3200
Power consumption	W	41	38
Current draw	A	0.16	0.13
Max. back pressure	Pa	80	120
Max. back pressure	inH2O	0.32	0.48
Min. ambient temperature	°C	-25	-25
Max. ambient temperature	°C	50	70
Starting current	A	0.25	0.21

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



W2S130-AA19-38

AC axial compact fan

Technical description


Weight	1.1 kg
Fan size	130 mm
Rotor surface	Painted black
Blade material	Sheet steel, painted black
Fan housing material	Die-cast aluminum, painted black
Number of blades	7
Airflow direction	"V"
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP20
Insulation class	"B"
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
Protection class	I (if protective earth is connected by customer to the housing's connection point)
Conformity with standards	EN 60335-1; CE



W2S130-AA19-38


AC axial compact fan

Product drawing



1	Direction of air flow "V"
2	Cable PVC 2x 0.5 mm ² , 2x crimped splices
3	M4 screw for fastening ground connector

Connection diagram




L1	blue
L2	brown
TOP	Thermal overload protector

W2S130-AA19-38

AC axial compact fan

Curves: Air performance 50 Hz



Measurement: LU-69605-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH2O
1	400	50	2800	41	0.16	350	0	205	0.00
2	400	50	2755	43	0.16	315	20	185	0.08
3	400	50	2740	44	0.16	270	40	160	0.16
4	400	50	2745	43	0.16	205	55	120	0.22


U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase



W2S130-AA19-38

AC axial compact fan

Curves: Air performance 60 Hz



Measurement: LU-69608-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	CFM	inH ₂ O
1	400	60	3200	38	0.13	395	0	230	0.00
2	400	60	3085	43	0.14	355	25	210	0.10
3	400	60	3025	44	0.14	300	50	175	0.20
4	400	60	3035	44	0.14	210	70	125	0.28

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

