


KARTA KATALOGOWA

W3G910-GU27-03

Wentylator osiowy EC HyBlade, łopatki sierpowe (seria S),
obudowa, z kratką ochronną


Producent: ebm-papst



Dane znamionowe		Budowa	
Napięcie znamionowe	3~ 400 V (380...480 V)	Wielkość	910 mm
Częstotliwość	50/60 Hz	Silnik	M3G150-IF
Prędkość obrotowa	970 obr/min	Materiał wirnika	wkładka z blachy aluminiowej natryskiwana tworzywem PP
Pobór mocy	2700 W	Obudowa	blacha stalowa ocynkowana, powlekana czarnym tworzywem (RAL 9005)
Pobór prądu	4,1 A	Obudowa elektroniki	odlew aluminiowy malowany na szaro
Maks. przeciwnieśnienie	210 Pa	Kratka ochronna	stal powlekana czarnym tworzywem (RAL 9005)
Temperatura otoczenia	-40...+60 °C	Liczba łopatek	5
Regulacja obrotów	MODBUS RTU	Kierunek obrotów	w prawo, patrząc na wirnik
Dane ErP (UE 327/2011)		Stopień ochrony	IP55
Sprawność całkowita	47,6 %	Klasa izolacji	F
Przepływ w pkt. optymalnym	22155 m³/h	Zabezpieczenie silnika	ochrona przed odwrotną polaryzacją i zablokowaniem wirnika
Przyrost ciśnienia	203 Pa	Łożyskowanie	kulkowe
Regulacja prędkości (ErP)	tak	Podłączenie	skrzynka zaciskowa
		Masa	49,2 kg

Charakterystyka przepływowa (50 Hz)

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-202155-1

Air performance measured according to ISO 5801 Installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Dane na okładce wg karty katalogowej producenta ebm-papst (oryginał na kolejnych stronach).

Wartości przy maksymalnym obciążeniu; producent zastrzega możliwość zmian.

Dobór, wycena i dostawa – zapytaj LUFTBERG

tel. +48 600 100 371 · tel. +48 604 959 199

biuro@luftberg.pl · www.luftberg.pl

W3G910-GU27-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	W3G910-GU27-03	
Motor	M3G150-IF	

Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60

Method of obtaining data		ml
Speed (rpm)	min ⁻¹	970
Power consumption	W	2700
Current draw	A	4.1
Max. back pressure	Pa	210
Max. back pressure	in. wg	0.84
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	47.6	36.3	09 Power consumption P_{ed}	kW	2.65
02 Measurement category		A		09 Air flow q_v	m ³ /h	22155
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	203
04 Efficiency grade N		51.3	40	10 Speed (rpm) n	min ⁻¹	965
05 Variable speed drive		Yes		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings). The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.

The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-202155



W3G910-GU27-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Technical description

Weight	49.2 kg
Size	910 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum, painted gray
Blade material	Sheet aluminum insert, sprayed with PP plastic
Fan housing material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Blade pitch	0°
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H2
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.3 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Reverse polarity and locked-rotor protection
Protection class	I (with customer connection of protective earth)



W3G910-GU27-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Conformity with standards	EN 61800-5-1; CE; UKCA
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC; UL 1004-7 + 60730-1




W3G910-GU27-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Product drawing



1	Airflow direction "V"
2	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm (The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)
3	Tightening torque 1.5 ± 0.2 Nm
4	Attachment holes for FlowGrid (91000-2-2957 not included in scope of delivery)


W3G910-GU27-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Connection diagram



No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V / PWM, Ri=100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Fan modulation level Characteristic curve parameterizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

W3G910-GU27-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Terminal/plug assignment

configurable IO functions: normal / inverse		electrical specification	configurable IO mode		OUTPUT																																																																																																																																																																																				
			active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D158 [0]	signal: tach out (selected directly via IO mode)	switch: fan enable / disable	D16A [...] D16C [...] D148 [...]	switch: set value source	switch: direction of rotation: cw / ccw	switch: control function: heating (pos.) / cooling (neg.)	source: set value	D101 [...] D147 [...] D104 [...]	switch: parameter set: #1 / #2	D12E [...] D12F [...]	switch: fan modulation level %	D130 [0]	signal: actual speed	D130 [1]	signal: system modulation level %	D130 [2]	signal: remote control output 0-10V	D130 [5]	pulse input for auto-addressing	D00C [1]	pulse output for auto-addressing	D130 [4]																																																																																																																																																															
IO1	MODBUS Register for IO mode configuration	D158 [2] RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz SELV U _{max} = 50VDC, I _{max} = 20mA SELV U _{max} = 50VDC, I _{max} = 20mA SELV	D158 [5] D158 [6]	D159 [0] D159 [2] D159 [3]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0] D15A [1] D15A [7] D15A [8]	D15A [4] D15A [5] D15A [6]	D15A [0]

○ configurable option

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.3




W3G910-GU27-03

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-202155-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa	cfm	in. wg
1	3~	400	50	970	1826	2.87	70	77	78	33705	0	19835	0.00
2	3~	400	50	970	2146	3.34	69	76	76	30525	70	17965	0.28
3	3~	400	50	970	2460	3.80	69	76	76	26930	140	15850	0.56
4	3~	400	50	970	2700	4.10	75	82	82	20980	210	12350	0.84
5	3~	400	50	850	1206	1.90	67	74	74	29350	0	17275	0.00
6	3~	400	50	850	1424	2.22	65	72	73	26620	53	15670	0.21
7	3~	400	50	850	1629	2.52	66	73	73	23480	107	13820	0.43
8	3~	400	50	850	1845	2.84	72	79	79	18530	164	10905	0.66
9	3~	400	50	700	674	1.06	62	69	69	24170	0	14225	0.00
10	3~	400	50	700	795	1.24	60	67	68	21925	36	12905	0.14
11	3~	400	50	700	910	1.41	61	68	68	19335	72	11380	0.29
12	3~	400	50	700	1030	1.59	67	74	74	15260	111	8980	0.45
13	3~	400	50	550	327	0.51	56	63	63	18995	0	11180	0.00
14	3~	400	50	550	386	0.60	54	61	62	17225	22	10140	0.09
15	3~	400	50	550	441	0.68	55	62	62	15190	45	8940	0.18
16	3~	400	50	550	500	0.77	61	68	68	11990	69	7060	0.28

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase

